



SUPER GRADER



Description

SUPER GRADER (G-2) is a bias tire particularly designed for graders. It shows excellent traction and self-cleaning features. SUPER GRADER is made of a special compound which enables an extended tire life-cycle and heavy-duty service.

UM

US Standard

Construction

⊠ Bias

Machinery

OTR ■ Grader

Version	STANDARD
Tire Type	TT
Tyre size	14.00-24
LI/SS	

Dimensions US Standard

USA Code	94062980
OD (US) (in)	52.6
SLR (US) (in)	24.3
RC (US) (in)	158.9
Rim Rec	8.00 TG SDC
Rim Alt	9.00/1.5 (DC); 10.00/VA SDC
TRA Code	G2

Load Capacity (US)

mph / psi	51
25	8050

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 28-02-2026

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..