



IS standard



GROWING TOGETHER

EARTHMAX

RADIAL OTR TIRES

SR 47 TP



PRODUCT DATA SHEET



Radial



EARTHMAX SR 47 TP

RADIAL OTR TIRES



EARTHMAX SR 47 TP (E-4) is an All-Steel radial tire specially engineered for rigid haul trucks operating in conditions requiring maximum traction and puncture resistance. The E-4 tread depth ensure long wear even on long hauls, thus reducing downtime and increasing productivity. EARTHMAX SR 47 TP is perfect for any task demanding both traction and stability particularly on muddy or slippery terrain. Available in standard and cut-resistant compounds.

Technologies



All Steel Radial



Extra Deep Tread

Performance



Traction



Stability



For muddy ground



High Puncture Resistance



Cut Resistance



Durability

Tire size	Type	TRA CODE	STAR RATING	LI/SS	Version	TKPH	O.W. (mm)	O.D. (mm)	SLR (mm)	RC (mm)	TREAD DEPTH (mm)	RIM		
												Rec.	Alt.	
Ø 35"	24.00 R 35	TL	E-4	**	209 B	CRC	333	670	2185	985	6625	73	17.00/3.5	-
	24.00 R 35	TL	E-4	**	209 B	STDC	390	670	2185	985	6625	73	17.00/3.5	-

CRC: Cut Resistance Compound - STDC: Standard Compound



Tolerances: O.D. ± 2% - O.W. ± 2% - RC ± 2.5% - LI/SS = Load Index / Speed Symbol; O.W. = Overall Width; O.D. = Overall Diameter; SLR = Static Loaded Radius; RC = Rolling Circumference