



US standard



GROWING TOGETHER

MULTIMAX

RADIAL MPT TIRES

MP 519



PRODUCT DATA SHEET



Radial



MULTIMAX MP 519

RADIAL MPT TIRES



MULTIMAX MP 519 is a particularly suitable tire for light trucks in all transport applications. The steel-belted casing provides excellent stability at high-speed (90 km/h - 60 mph). Thanks to its low rolling resistance, the tire ensures reduced fuel consumption.

Technologies



High Speed

Performance



Fuel Economy



Stability

	US CODE	Tire size	Type	PR	LI/SS	Version	O.D.	S.W.	SLR	RC	TREAD DEPTH (32nds)	TIRE WEIGHT (lbs)	RIM	
							(In.)	(In.)	(In.)	(In.)			Rec.	Alt.
Ø 16"	94053384	7.50 R 16 LT	TL	6	109/107 G	STD					12	463	6.00	5.50 F; 6 L; 7 L
	94063437	7.50 R 16 LT	TL	8	112/110 G	STD					12	48	6.00	5.50 F; 6 L; 7 L

STD: Standard



Tolerances: O.D. ± 2% - S.W. ± 2% - RC ± 2.5% - LI/SS = Load Index / Speed Symbol; S.W. = Section Width; O.D. = Overall Diameter; SLR = Static Loaded Radius; RC = Rolling Circumference