



GF 304

Description

GF 304 is suitable for golf applications with golf carts. GF 304 ensures best comfort and turf protection. GF 304 is also available as "aramid-belted" version to provide increased puncture resistance.

UM

US Standard

Construction

 Bias

Machinery

Agriculture ▪ Golf Kart



Version	STANDARD
Tire Type	TL
Tyre size	18x8.50-8
LI/SS	

Dimensions US Standard

USA Code	94031078
SW (US) (in)	8.5
OD (US) (in)	18.1
SLR (US) (in)	8.0
RC (US) (in)	52.5
Rim Rec	7.00 - 55; - 70; - 90
ECE	E11-106R-005197

Load Capacity (US)

mph / psi	34
10	1050

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 28-02-2026

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..