



EARTHMAX SR 30



Description

EARTHMAX SR 30 (E-3/L-3) is an All Steel radial tire specifically designed and purpose-built for loaders and articulated dump trucks. It features steel belts and the rigid block pattern providing excellent stability and durability. The special cut-resistant compound makes EARTHMAX SR 30 the ideal solution for a variety of demanding working conditions.

UM

IS Standard

Construction

 Radial

Machinery

OTR ■ Rigid Dump Truck

Version CUT RESISTANT COMPOUND

Tire Type TL

Tyre size 20.5R25

LI/SS 193;A2

Dimensions IS Standard

OD (IS) (mm)	1487
SLR (IS) (mm)	663
RC (IS) (mm)	4439
Rim Rec	17.00/2.0
Rim Alt	17.00/1.7
TRA Code	L3

Load Capacity (IS)

km/h / bar	05:25:00	05:50:00	06:15:00	06:00:00	06:25:00	06:50:00													
10	9750	10000	10300	10900	11200	11500													

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different L condition.

Printed on 24-02-2026

All product data contained in this publication are for information purposes only and may be modified at any time without notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for errors or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without the written consent by Balkrishna Industries Ltd..