



IS standard



GROWING TOGETHER

SNOW-RIDE (A)



PRODUCT DATA SHEET



Bias



SNOW-RIDE (A)

SNOW-RIDE is particularly suitable for municipality and maintenance applications in winter conditions with compact loaders and skid steers. It features excellent traction and is ideal for ice and snow operations. Its specially designed tread pattern eliminates slippage risks and ensures a longer tyre life-cycle.

Technologies



Snow Pattern



Strong Casing

Performance



Durability



Traction

	Tyre size	Type	PR	LI/SS	Version	S.W. (mm)	O.D. (mm)	SLR (mm)	RC (mm)	RIM	
										Rec.	Alt.
Ø 16"	12.5/70 - 16	TL	6	-	STD	315	850	385	2550	10 LB	-
	12.5/70 - 16	TL	10	-	STD	315	850	385	2550	10 LB	-
Ø 16.5"	10 - 16.5	TL	6	-	STD	270	780	357	2340	8.25	-
	10 - 16.5	TL	10	-	STD	270	780	357	2340	8.25	-
	12 - 16.5	TL	6	-	STD	305	835	379	2505	9.75	-
	12 - 16.5	TL	10	-	STD	305	835	379	2505	9.75	-
Ø 18"	15.5/60 - 18	TL	10	-	STD	395	938	425	2814	W 13	-
Ø 20"	17.5/65 - 20	TL	10	-	STD	445	1095	485	3124	W 14 L	-

STD: Standard



Tolerances: O.D. ± 2% - S.W. ± 2% - RC ± 2.5% - LI/SS = Load Index / Speed Symbol; S.W. = Section Width; O.D. = Overall Diameter; SLR = Static Loaded Radius; RC = Rolling Circumference