



AGRIMAX V-FLECTO

Description

AGRIMAX V-FLECTO is BKT's response to the challenging demand of both technology and performance for high-power tractors. This tire is perfect for soil tillage and haulage applications thanks to reduced soil compaction and self-cleaning properties. With the innovative VF technology, AGRIMAX V-FLECTO can carry heavy loads with a lower inflating pressure compared to standard and IF tires, reaching high speeds. It also features the Narrow Rim Option that allows mounting standard rims on the tire. BKT has designed this tire with optimized geometry to enhance driving comfort both in the fields and on the road reducing fuel consumption.



UM

IS Standard

Construction

 Radial

Machinery

Agriculture ■ High-Power Tractor

Version	STANDARD
Tire Type	TL
Tyre size	VF520/85R42
LI/SS	180;D

Dimensions IS Standard

SW (IS) (mm)	535
OD (IS) (mm)	1951
SLR (IS) (mm)	876
RC (IS) (mm)	5841
Rim Rec	DW 18 L
ECE	E11-106R-007169
TRA Code	R1W

Load Capacity (IS)

km/h / bar	0.6	0.8	1	1.2	1.4	1.6	2	2.4	3.2
70	2840	3350	3860	4300	4805	5245	5755	6190	7280
from 65 to 40	3120	3680	4240	4720	5280	5760	6320	6800	8000
30	3185	3755	4325	4815	5390	5880	6450	6940	8160
20	3245	3830	4410	4910	5495	5995	6575	7075	8320
10	3435	4050	4665	5195	5810	6340	6955	7480	8800
Upto 10 Cyc with front loader	4370	5155	5940	6610	7395	8065	8850	9520	11200
10HT	3185	3755	4325	4815	5390	5880	6450	6940	8160

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 28-02-2026

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..