



## RIB MASTER



### Description

RIB MASTER is suitable for transport and hay harvesting operations with trailers, balers and implement machinery. This tire offers great load capacity and a long tire life-cycle.

### UM

IS Standard

### Construction

◇ Bias

### Machinery

Agriculture ■ Baler

Version	STANDARD
Tire Type	TL
Tyre size	215/75-17.5
LI/SS	

## Dimensions IS Standard

SW (IS) (mm)	220
OD (IS) (mm)	775
SLR (IS) (mm)	360
RC (IS) (mm)	2310
Rim Rec	6.75
ECE	E11-106R-004593

## Load Capacity (IS)

km/h / bar	9.00
10 FR	3710
25 FR	3155
30 FR	2970
40 FR	2650

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 28-02-2026

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..