



## MULTIMAX MP 525

### Description

MULTIMAX MP 525 is an All-Steel multi-purpose radial tire designed for telehandlers, compact loaders, and graders in agro-industrial applications. The tire has been specifically developed to carry heavy loads at higher speeds both on and off the road. The large non-directional tread design provides exceptional traction on any surface. The strong sidewall ensures exceptional lateral stability, making it the ideal choice for agricultural and material handling operations.



### UM

IS Standard

### Construction

 Radial

### Machinery

Agriculture ▪ Universal Vehicle, Industrial & Construction ▪ Compact Loader

Version	STANDARD
Tire Type	TL
Tyre size	405/70R18
LI/SS	146;J

## Dimensions IS Standard

OD (IS) (mm)	1025
SLR (IS) (mm)	462
RC (IS) (mm)	3122
Rim Rec	13
Rim Alt	11; 12
ECE	E11-54R-0022030

## Load Capacity (IS)

km/h / bar	3.75	4.00
100	2800	3000
50	2575	-
10	3650	-

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 28-02-2026

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..