



US standard



GROWING TOGETHER

# FL 639



PRODUCT DATA SHEET



Radial



184



# FL 639

FL 639 is a field-oriented flotation radial tire also suitable for spreading applications. Its wide footprint area ensures low soil compaction resulting in increased crop productivity. The reinforced bead and the sidewall protection contribute to an extended tire life-cycle. FL 639 ensures extraordinary traction along with great self-cleaning properties.

**Technologies**



Reinforced Bead



High Speed

**Performance**



Reduced Soil Compaction



Traction



Self-Cleaning



Durability

|         | US CODE  | Tire size      | LI/SS            |    | RIM      |      | S.W.<br>(In.) | O.D.<br>(In.) | SLR<br>(In.) | RC<br>(In.) | TREAD DEPTH<br>(32nds) | TIRE WEIGHT<br>(lbs) | Version |
|---------|----------|----------------|------------------|----|----------|------|---------------|---------------|--------------|-------------|------------------------|----------------------|---------|
|         |          |                | DW               | FR | Rec.     | Alt. |               |               |              |             |                        |                      |         |
| Ø 22.5" | 94034260 | 560/45 R 22.5  | 152 D/<br>163 A8 |    | AG 16.00 | -    | 21.4          | 42.4          | 19.1         | 130.0       | 36                     | 214                  | STD     |
|         | 94028153 | 600/50 R 22.5  | 159 D/<br>170 A8 |    | AG 20.00 | -    | 24.1          | 46.1          | 20.9         | 139.4       | 38                     | 241                  | STD     |
|         | 94063239 | 600/50 R 22.5  | 156 B<br>168 B   |    | AG 20.00 | -    | 24.1          | 46.1          | 20.5         | 141.4       | 38                     | 244                  | STD     |
|         | 94063246 | 710/40 R 22.5  | 158 B<br>170 B   |    | AG 24.00 | -    | 28.6          | 44.9          | 19.8         | 137.5       | 37                     | 275                  | STD     |
|         | 94041176 | 710/40 R 22.5  | 161 D/<br>172 A8 |    | AG 24.00 | -    | 28.6          | 44.9          | 19.8         | 137.5       | 37                     | 278                  | STD     |
|         | 94513420 | 800/40 R 22.5  | 168 D/<br>178 A8 |    | AG 28.00 | -    | 32.6          | 47.7          | 21.2         | 143.4       | 38                     | 334                  | STD     |
|         |          | <b>NEWSIZE</b> |                  |    |          |      |               |               |              |             |                        |                      |         |
| Ø 26.5" | 94064779 | 850/40 R 26.5  | 173 D/<br>184 A8 |    | AG 28.00 | -    | 33.9          | 53.3          | 23.6         | 162.3       | 39                     | 433                  | STD     |

STD: Standard



Tolerances: O.D. ± 2% - S.W. ± 2% - RC ± 2.5% - LI/SS = Load Index / Speed Symbol; S.W. = Section Width; O.D. = Overall Diameter; SLR = Static Loaded Radius; RC = Rolling Circumference; DW = Drive Wheel; FR = Free Rolling