



TR 463

Description

TR 463 has been specially designed for backhoe loaders and industrial tractors. Made of a superior tread compound and featuring a strong nylon casing, this tire stands for best results in industrial and OTR applications, and on construction sites. TR 463 provides excellent traction for drive wheels.

UM

US Standard

Construction

 Bias

Machinery

Industrial & Construction ■ Backhoe Loader



Version	INDUSTRIAL
Tire Type	TL
Tyre size	16.9-24
LI/SS	152;A8

Dimensions US Standard

USA Code	94515172
SW (US) (in)	17.5
OD (US) (in)	51.2
SLR (US) (in)	23.0
RC (US) (in)	152.6
Rim Rec	DW 15 L
Rim Alt	DW 14 L
TRA Code	R4

Load Capacity (US)

mph / psi	38
25	7850

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 28-02-2026

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..