



IS standard



GROWING TOGETHER

# XL GRIP (T)



PRODUCT DATA SHEET



Bias



# XL GRIP (T)

XL GRIP (E-3) best suits on/off trucks carrying heavy loads in mining applications. Its tread compound is designed to minimize cuts and punctures on harshest ground conditions. XL GRIP (E-3) offers exceptional traction and provides an extended tire life-cycle.

## Performance



Tire size	Type	TRA CODE	PR	LI/SS	Version	TKPH	O.W. (mm)	O.D. (mm)	SLR (mm)	RC (mm)	TREAD DEPTH (mm)	RIM		
												Rec.	Alt.	
Ø 16"	8.25 - 16	TT	-	16	-	STD	-	238	870	-	-	19.5	6.50 H	6.00 G
	Ø 20"	10.00 - 20	TT	-	18	-	STD	-	285	1075	505	3257	22	7.5
	11.00 - 20	TT	-	18	-	STD	-	297	1115	529	3368	24.5	8.0	7.5
	12.00 - 20	TT	-	18	-	STD	-	320	1155	545	3465	24	8.5	8.0
	12.00 - 20	TT	-	20	-	STD	-	320	1155	545	3465	24	8.5	8.0
	12.00 - 20	TT	-	24	-	STD	-	320	1155	545	3465	24	8.5	8.0
Ø 24"	12.00 - 24	TT	-	20	-	STD	-	320	1250	585	3710	24	8.5	8.0
	12.00 - 24	TL	-	20	-	STD	-	320	1250	585	3710	24	8.5	8.0
	12.00 - 24	TT	-	24	-	STD	-	320	1250	585	3710	24	8.5	8.0

STD: Standard



Tolerances: O.D. ± 2% - O.W. ± 2% - RC ± 2.5% - LI/SS = Load Index / Speed Symbol; O.W. = Overall Width; O.D. = Overall Diameter; SLR = Static Loaded Radius; RC = Rolling Circumference