



AGRIMAX RT 657



Description

AGRIMAX RT 657 is the ideal tire for on-the-road usage and soil tillage; some sizes are also suitable for vineyard harvesting. This tire guarantees excellent driving comfort as well as significant fuel savings. It has a high load capacity also at high speed levels. AGRIMAX RT 657 is the best choice for those who need a versatile and reliable tire, with no compromise on performance.

UM

IS Standard

Construction

 Radial

Machinery

Agriculture ■ Vineyard Harvester

Version STANDARD

Tire Type TL

Tyre size 420/65R30

LI/SS 136;D

Dimensions IS Standard

SW (IS) (mm)	418
OD (IS) (mm)	1308
SLR (IS) (mm)	606
RC (IS) (mm)	3952
Rim Rec	W 13
Rim Alt	W 12; W 11
ECE	E11-106R-002975
TRA Code	R1W

Load Capacity (IS)

km/h / bar	0.6	0.8	1.0	1.2	1.4	1.6	2.0	2.4
65	1055	1210	1390	1570	1750	1930	2085	2240
50	1110	1275	1465	1650	1840	2030	2195	2355
40	1145	1315	1510	1705	1900	2090	2260	2430
30	1215	1395	1600	1810	2015	2220	2400	2580
10 LT	1415	1625	1865	2105	2345	2585	2795	3005
10 HT	1215	1395	1600	1810	2015	2220	2400	2580

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 28-02-2026

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..