



PAC MASTER



Description

PAC MASTER is a bias tire for compactors. It shows high stability and ensures an extended tire life-cycle. It is made of a special compound that provides particular heat resistance.

UM

US Standard

Construction

 Bias

Machinery

Industrial & Construction ■ Compactor

Version	STANDARD
Tire Type	TT
Tyre size	9.00-20
LI/SS	

Dimensions US Standard

USA Code	94002665
SW (US) (in)	10.8
OD (US) (in)	40.0
SLR (US) (in)	18.5
RC (US) (in)	122.3
Rim Rec	7.0
Rim Alt	7.5
ECE	E11-106R-005360

Load Capacity (US)

mph / psi	120
5	10500
10	8270

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 28-02-2026

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..