



IS standard



GROWING TOGETHER

SNOW - RIDE (B)



PRODUCT DATA SHEET



Bias



Technologies



Snow Pattern

Performance



Cut and Chip Resistance



Durability



Heavy Duty



Ice and Snow



Stability



SNOW - RIDE (B)

SNOW-RIDE is particularly suitable for road applications in winter conditions with skid steers. It features excellent traction and is ideal for ice and snow operations. Its specially designed tread pattern eliminates slippage risks.

	Tire size	Type	PR	LI/SS	Version	S.W. (mm)	O.D. (mm)	SLR (mm)	RC (mm)	RIM	
										Rec.	Alt.
Ø 24"	16.9 - 24	TL	12	149 A8	STD	429	1310	602	3908	DW 15 L	DW 14 L
	18.4 - 24	TL	12	155 A8	STD	480	1375	617	4050	DW 16 L	DW 15 L
Ø 25"	15.5 - 25	TL	12	-	STD	395	1280	569	3818	12.00/1.3	-
	17.5 - 25	TL	12	-	STD	445	1348	608	4044	14.00/1.5	-
	17.5 - 25	TL	16	-	STD	445	1348	608	4044	14.00/1.5	-
	20.5 - 25	TL	16	-	STD	537	1492	652	4423	17.00/2.0	17.00/1.7
	23.5 - 25	TL	16	-	STD	612	1630	693	4800	19.50/2.5	-

STD: Standard



Tolerances: O.D. ± 2% - S.W. ± 2% - RC ± 2.5% - LI/SS = Load Index / Speed Symbol; S.W. = Section Width; O.D. = Overall Diameter; SLR = Static Loaded Radius; RC = Rolling Circumference