



RIDEMAX FL 693 M



Description

RIDEMAX FL 693 M is the ideal radial tire for those who frequently travel on the road with trailers/tank trucks. Actually designed for 75% on-the-road use, RIDEMAX FL 693 M provides excellent road performance prioritizing both comfort and self-cleaning properties. The speed index classes D/E of the range stands for higher speeds when travelling on the road leading to significant time savings.

UM

US Standard

Construction

 Radial

Machinery

Agriculture ■ Tanker

Version	STANDARD
Tire Type	TL
Tyre size	710/45R22.5
LI/SS	165;D

Dimensions US Standard

USA Code	94062447
SW (US) (in)	27.8
OD (US) (in)	47.7
SLR (US) (in)	21.3
RC (US) (in)	144.0
Rim Rec	AG 24.00
ECE	E11-106R-005994

Load Capacity (US)

mph / psi	15	17	23	29	35	41	46	52	58
45	3780	4240	5270	6000	6920	7860	8580	9400	10330
40	4140	4660	5800	6590	7620	8630	9420	10340	11350
30	5030	5640	7010	7980	9210	10450	11420	12510	13750
25	5640	6340	7880	8960	10350	11740	12820	14050	15440
20	6260	7030	8750	9950	11500	13040	14240	15610	17150
15	6560	7360	9160	10420	12030	13650	14900	16340	17940
5	7460	8390	10430	11860	13700	15540	16960	18610	20440

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 28-02-2026

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..