



AGRIMAX RT 955



Description

AGRIMAX RT 955 is a BKT radial tire for row crop applications, while some sizes are also suitable for spraying and vineyards. The special tread design with a rounded shoulder provides excellent traction performance, stability and self-cleaning properties. Thanks to its strong casing, AGRIMAX RT 955 has a high load capacity.

UM

IS Standard

Construction

 Radial

Machinery

Agriculture ■ Sprayer

Version	STANDARD
Tire Type	TL
Tyre size	230/95R44
LI/SS	134;A8/B

Dimensions IS Standard

SW (IS) (mm)	228
OD (IS) (mm)	1556
SLR (IS) (mm)	739
RC (IS) (mm)	4788
Rim Rec	W 7
Rim Alt	W 8
ECE	E4-106R-000777
TRA Code	R1

Load Capacity (IS)

km/h / bar	0.8	1.2	1.6	2.0	2.4	2.8	3.2	3.6	4.0	4.4
50	830	1085	1315	1445	1530	1675	1825	1975	2120	-
40	830	1085	1315	1445	1530	1675	1825	1975	2120	-
30	890	1160	1410	1545	1635	1795	1955	2115	2270	-
10	990	1245	1530	1815	2100	2165	2420	2675	2930	3180

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 28-02-2026

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..