



IS standard



GROWING TOGETHER

TR 135



PRODUCT DATA SHEET



Bias



Technologies



Special Compound



Reinforced Carcass

Performance



Traction



High Load Capacity



Self-Cleaning



Durability



Cut and Chip Resistance



TR 135

TR 135 is best suitable for tractors in soil tillage applications. Its reinforced casing and the special cut-and-chip resistance compound provide an extended tire life-cycle. Traction, self-cleaning properties and load capacity are key features which make the TR 135 tire the ideal partner even on the most difficult ground conditions.

	Tire size	RIM		S.W. (mm)	O.D. (mm)	SLR (mm)	RC (mm)	Version	PR	Type	LI/SS
		Rec.	Alt.								
Ø 16"	12.4 - 16	W 11	W 9; 9; W 10	326	960	431	2852	STD	4	TT	97 A6
	12.4 - 16	W 11	W 9; 9; W 10	326	960	431	2852	STD	8	TT	111 A6
Ø 20"	8.00 - 20	5.50 F	-	225	965	448	2837	STD	6	TT	105 A6
	8.00 - 20	5.50 F	-	225	965	448	2837	STD	8	TT	111 A6
	9.5 - 20	W 8	W 7	240	955	454	2888	STD	6	TT	102 A6
	9.5 - 20	W 8	W 7	240	955	444	2881	HD	8	TT	107 A6
	9.5 - 20	W 8	W 7	240	955	454	2888	STD	8	TT	107 A6
	10.00 - 20	7.5	-	280	1075	495	3160	STD	10	TT	152 A2
	11.2 - 20	W 10	W 9; 9	292	1020	466	3077	STD	8	TT	111 A6
	12.4 - 20	W 11	W 9; 9; W 10; 11	325	1075	500	3160	HD	8	TT	116 A6
	12.4 - 20	W 11	W 9; 9; W 10; 11	325	1075	500	3160	STD	8	TT	116 A6
Ø 24"	8.3 - 24	W 7	W 6	211	995	469	2985	STD	6	TT	100 A6
	8.3 - 24	W 7	W 6	211	995	469	2985	HD	8	TT	105 A6
	8.3 - 24	W 7	W 6	211	995	475	3076	STD	8	TT	105 A6

STD: Standard - HD: Heavy Duty

Tolerances: O.D. ± 2% - S.W. ± 2% - RC ± 2.5% - LI/SS = Load Index / Speed Symbol; S.W. = Section Width; O.D. = Overall Diameter; SLR = Static Loaded Radius; RC = Rolling Circumference



Bias

R-1

A6

168

Technologies



Special Compound



Reinforced Carcass

Performance



Traction



High Load Capacity



Self-Cleaning



Durability



Cut and Chip Resistance



	Tire size	RIM		S.W. (mm)	O.D. (mm)	SLR (mm)	RC (mm)	Version	PR	Type	LI/SS
		Rec.	Alt.								
Ø 24"	8.3 - 24	W 7	W 6	211	995	469	2985	HD	10	TT	111 A6
	9.5 - 24	W 8	W 7	241	1060	502	3234	STD	6	TT	106 A6
	9.5 - 24	W 8	W 7	241	1060	502	3234	HD	8	TT	112 A6
	9.5 - 24	W 8	W 7	241	1060	502	3234	STD	8	TT	112 A6
	9.5 - 24	W 8	W 7	241	1060	502	3234	HD	10	TT	116 A6
	9.5 - 24	W 8	W 7	241	1060	502	3234	STD	10	TT	116 A6
	11.2 - 24	W 10	W 9	284	1105	517	3399	STD	6	TT	110 A6
	11.2 - 24	W 10	W 9	284	1105	507	3303	HD	8	TT	116 A6
	11.2 - 24	W 10	W 9	284	1105	517	3399	STD	8	TT	116 A6
	11.2 - 24	W 10	W 9	284	1105	517	3399	STD	8	TL	116 A6
	11.2 - 24	W 10	W 9	284	1105	517	3399	HD	10	TL	120 A6
	11.2 - 24	W 10	W 9	284	1105	517	3399	HD	10	TT	120 A6
	12.4 - 24	W 11	W 9; W 10	315	1160	543	3573	STD	6	TT	115 A6
	12.4 - 24	W 11	W 9; W 10	315	1160	531	3477	HD	8	TT	121 A6

STD: Standard - HD: Heavy Duty

Tolerances: O.D. ± 2% - S.W. ± 2% - RC ± 2.5% - LI/SS = Load Index / Speed Symbol; S.W. = Section Width; O.D. = Overall Diameter; SLR = Static Loaded Radius; RC = Rolling Circumference



Bias



Technologies



Special Compound



Reinforced Carcass

Performance



Traction



High Load Capacity



Self-Cleaning



Durability



Cut and Chip Resistance



	Tire size	RIM		S.W. (mm)	O.D. (mm)	SLR (mm)	RC (mm)	Version	PR	Type	LI/SS
		Rec.	Alt.								
Ø 24"	12.4 - 24	W 11	W 9 ; W 10	315	1160	531	3477	HD	8	TL	121 A6
	12.4 - 24	W 11	W 9 ; W 10	315	1160	543	3573	STD	8	TT	121 A6
	12.4 - 24	W 11	W 9 ; W 10	315	1160	543	3573	STD	8	TL	121 A6
	12.4 - 24	W 11	W 9 ; W 10	315	1160	543	3573	STD	10	TT	125 A6
	12.4 - 24	W 11	W 9 ; W 10	315	1160	543	3573	SPL	12	TT	128 A6
	12.4 - 24	W 11	W 9 ; W 10	315	1160	543	3573	STD	12	TT	128 A6
	12.4 - 24	W 11	W 9 ; W 10	315	1160	543	3573	STD	12	TL	128 A6
	13.6 - 24	W 12	W 11	355	1220	562	3698	HD	8	TT	123 A6
	13.6 - 24	W 12	W 11	355	1220	562	3698	STD	8	TT	123 A6
	13.6 - 24	W 12	W 11	355	1220	562	3698	STD	8	TL	123 A6
	13.6 - 24	W 12	W 11	355	1220	562	3698	HD	12	TT	130 A6
	13.6 - 24	W 12	W 11	355	1220	562	3698	STD	12	TT	130 A6
14.9 - 24	W 13	W 11 ; W 12	378	1265	570	3769	HD	8	TT	128 A6	
14.9 - 24	W 13	W 11 ; W 12	378	1265	570	3769	HD	8	TL	128 A6	

STD: Standard - HD: Heavy Duty - SPL: Special

Tolerances: O.D. ± 2% - S.W. ± 2% - RC ± 2.5% - LI/SS = Load Index / Speed Symbol; S.W. = Section Width; O.D. = Overall Diameter; SLR = Static Loaded Radius; RC = Rolling Circumference



Bias



Technologies



Special Compound



Reinforced Carcass

Performance



Traction



High Load Capacity



Self-Cleaning



Durability



Cut and Chip Resistance



	Tire size	RIM		S.W. (mm)	O.D. (mm)	SLR (mm)	RC (mm)	Version	PR	Type	LI/SS
		Rec.	Alt.								
Ø 24"	14.9 - 24	W 13	W 11 ; W 12	378	1265	576	3837	STD	8	TT	128 A6
	14.9 - 24	W 13	W 11 ; W 12	378	1265	576	3837	STD	8	TL	128 A6
	14.9 - 24	W 13	W 11 ; W 12	378	1265	576	3837	HD	10	TL	132 A6
	14.9 - 24	W 13	W 11 ; W 12	378	1265	576	3837	HD	12	TT	135 A6
	14.9 - 24	W 13	W 11 ; W 12	378	1265	576	3837	STD	12	TT	135 A6
	14.9 - 24	W 13	W 11 ; W 12	378	1265	576	3837	STD	12	TL	135 A6
	16.9 - 24	W 15 L	W 14 L	429	1335	613	3925	HD	8	TT	133 A6
	16.9 - 24	W 15 L	W 14 L	429	1335	613	3925	STD	8	TL	133 A6
	16.9 - 24	W 15 L	W 14 L	429	1335	613	3925	STD	8	TT	133 A6
	16.9 - 24	W 15 L	W 14 L	429	1335	613	3925	STD	10	TL	136 A6
	16.9 - 24	W 15 L	W 14 L	429	1335	613	3925	STD	10	TT	136 A6
	16.9 - 24	W 15 L	W 14 L	429	1335	613	3925	HD	12	TT	140 A6
Ø 26"	14.9 - 26	W 13	W 11 ; W 12	375	1315	599	3947	HD	8	TT	129 A6
	14.9 - 26	W 13	W 11 ; W 12	375	1315	599	3947	STD	8	TT	129 A6

STD: Standard - HD: Heavy Duty

Tolerances: O.D. ± 2% - S.W. ± 2% - RC ± 2.5% - LI/SS = Load Index / Speed Symbol; S.W. = Section Width; O.D. = Overall Diameter; SLR = Static Loaded Radius; RC = Rolling Circumference



Bias



A6



Technologies



Special Compound



Reinforced Carcass

Performance



Traction



High Load Capacity



Self-Cleaning



Durability



Cut and Chip Resistance



	Tire size	RIM		S.W. (mm)	O.D. (mm)	SLR (mm)	RC (mm)	Version	PR	Type	LI/SS
		Rec.	Alt.								
Ø 26"	14.9 - 26	W 13	W 11 ; W 12	375	1315	599	3947	STD	12	TT	136 A6
	16.9 - 26	W 15 L	W 14 L	430	1380	625	4183	STD	10	TT	137 A6
	16.9 - 26	W 15 L	W 14 L	430	1380	625	4183	STD	10	TL	137 A6
	16.9 - 26	W 15 L	W 14 L	430	1380	625	4183	STD	12	TT	140 A6
	23.1 - 26	DW 20 B ; DW 20 A	-	587	1585	700	4615	DB	12	TL	153 A6
	23.1 - 26	DW 20 B ; DW 20 A	-	587	1585	700	4615	DB	12	TT	153 A6
	23.1 - 26	DW 20 B ; DW 20 A	-	587	1585	700	4615	STD	12	TL	153 A6
	23.1 - 26	DW 20 B ; DW 20 A	-	587	1585	700	4615	STD	12	TT	153 A6
	23.1 - 26	DW 20 B ; DW 20 A	-	587	1585	700	4615	STD	14	TL	156 A6
	23.1 - 26	DW 20 B ; DW 20 A	-	587	1585	700	4615	DB	16	TL	159 A6
	23.1 - 26	DW 20 B ; DW 20 A	-	587	1585	700	4615	DB HD	16	TL	159 A6
	23.1 - 26	DW 20 B ; DW 20 A	-	587	1585	700	4615	HD	16	TT	159 A6
	23.1 - 26	DW 20 B ; DW 20 A	-	587	1585	700	4615	STD	16	TL	159 A6
	23.1 - 26	DW 20 B ; DW 20 A	-	587	1585	700	4615	STD	16	TT	159 A6

STD: Standard - DB: Dual Bead - HD: Heavy Duty - DB HD: Dual Bead Heavy Duty

Tolerances: O.D. ± 2% - S.W. ± 2% - RC ± 2.5% - LI/SS = Load Index / Speed Symbol; S.W. = Section Width; O.D. = Overall Diameter; SLR = Static Loaded Radius; RC = Rolling Circumference



Bias



Technologies



Special Compound



Reinforced Carcass

Performance



Traction



High Load Capacity



Self-Cleaning



Durability



Cut and Chip Resistance



	Tire size	RIM		S.W. (mm)	O.D. (mm)	SLR (mm)	RC (mm)	Version	PR	Type	LI/SS
		Rec.	Alt.								
Ø 26"	23.1 - 26	DW 20 B ; DW 20 A	-	587	1585	700	4615	DB	18	TL	161 A6
Ø 28"	8.3 - 28	W 7	W 6	213	1104	519	3347	STD	6	TT	103 A6
	8.3 - 28	W 7	W 6	213	1104	519	3347	STD	8	TT	108 A6
	9.5 - 28	W 8	W 7	235	1155	548	3557	STD	6	TT	108 A6
	9.5 - 28	W 8	W 7	235	1155	548	3557	STD	8	TT	114 A6
	11.2 - 28	W 10	W 9	284	1205	565	3543	HD	8	TT	118 A6
	11.2 - 28	W 10	W 9	284	1205	565	3543	STD	8	TT	118 A6
	11.2 - 28	W 10	W 9	284	1205	565	3543	STD	10	TT	122 A6
	12.4 - 28	W 11	W 9 ; W 10	325	1260	584	3876	STD	6	TT	117 A6
	12.4 - 28	W 11	W 9 ; W 10	325	1260	584	3876	HD	8	TT	123 A6
	12.4 - 28	W 11	W 9 ; W 10	325	1260	584	3876	STD	8	TT	123 A6
	12.4 - 28	W 11	W 9 ; W 10	325	1260	584	3876	STD	10	TT	127 A6
	12.4 - 28	W 11	W 9 ; W 10	325	1260	584	3876	STD	12	TT	131 A6
	13.6 - 28	W 12	W 11	345	1310	607	4023	HD	8	TT	125 A6

STD: Standard - DB: Dual Bead - HD: Heavy Duty

Tolerances: O.D. ± 2% - S.W. ± 2% - RC ± 2.5% - LI/SS = Load Index / Speed Symbol; S.W. = Section Width; O.D. = Overall Diameter; SLR = Static Loaded Radius; RC = Rolling Circumference



Bias



Technologies



Special Compound



Reinforced Carcass

Performance



Traction



High Load Capacity



Self-Cleaning



Durability



Cut and Chip Resistance



	Tire size	RIM		S.W. (mm)	O.D. (mm)	SLR (mm)	RC (mm)	Version	PR	Type	LI/SS
		Rec.	Alt.								
Ø 28"	13.6 - 28	W 12	W 11	345	1310	606	3908	STD	8	TT	125 A6
	13.6 - 28	W 12	W 11	345	1310	606	3908	STD	12	TT	134 A6
	13.6 - 28	W 12	W 11	345	1310	606	3908	STD	14	TT	137 A6
	14.9 - 28	W 13	W 11 ; W 12	378	1365	634	4170	STD	6	TT	125 A6
	14.9 - 28	W 13	W 11 ; W 12	378	1365	634	4170	HD	8	TT	130 A6
	14.9 - 28	W 13	W 11 ; W 12	378	1365	634	4170	STD	8	TT	130 A6
	14.9 - 28 (28)	W 13	W 11 ; W 12	378	1365	634	4170	STD	8	TL	130 A6
	14.9 - 28	W 13	W 11 ; W 12	378	1365	634	4170	HD	12	TT	137 A6
	14.9 - 28	W 13	W 11 ; W 12	378	1365	634	4170	STD	12	TT	137 A6
	14.9 - 28	W 13	W 11 ; W 12	378	1365	634	4170	STD	14	TT	139 A6
	18.4 - 28	W 16 L	W 15 L	467	1501	691	4413	STD	8	TL	138 A6
	18.4 - 28	W 16 L	W 15 L	467	1501	691	4413	STD	12	TL	147 A6
Ø 30"	7.2 - 30	W 6	-	185	1095	523	3219	STD	6	TT	95 A6
	9.5 - 30	W 8	W 7	241	1200	567	3528	STD	6	TT	109 A6

STD: Standard - HD: Heavy Duty

Tolerances: O.D. ± 2% - S.W. ± 2% - RC ± 2.5% - LI/SS = Load Index / Speed Symbol; S.W. = Section Width; O.D. = Overall Diameter; SLR = Static Loaded Radius; RC = Rolling Circumference



Bias



A6



Technologies



Special Compound



Reinforced Carcass

Performance



Traction



High Load Capacity



Self-Cleaning



Durability



Cut and Chip Resistance



	Tire size	RIM		S.W. (mm)	O.D. (mm)	SLR (mm)	RC (mm)	Version	PR	Type	LI/SS
		Rec.	Alt.								
Ø 30"	9.5 - 30	W 8	W 7	241	1200	567	3528	STD	8	TT	115 A6
	14.9 - 30	W 13	W 11 ; W 12	378	1415	659	4316	STD	8	TT	131 A6
	15 - 30 (18.4 - 30)	W 16 L	W 15 L	460	1545	714	4542	STD	12	TT	149 A6
	15 - 30 (18.4 - 30)	W 16 L	W 15 L	460	1545	714	4542	STD	14	TT	151 A6
	16.9 - 30	W 15 L	W 14 L	429	1485	678	4535	STD	8	TT	137 A6
	16.9 - 30	W 15 L	W 14 L	429	1485	678	4535	STD	10	TT	139 A6
	16.9 - 30 (14 - 30)	W 15 L	W 14 L	429	1485	678	4535	STD	14	TT	146 A6
	16.9 - 30 (14 - 30)	W 15 L	W 14 L	429	1485	678	4535	STD	16	TT	149 A6
	18.4 - 30	W 16 L	W 15 L	460	1545	697	4712	HD	8	TT	139 A6
	18.4 - 30	W 16 L	W 15 L	460	1545	697	4712	STD	8	TT	139 A6
	18.4 - 30	W 16 L	W 15 L	460	1545	697	4712	HD	10	TT	145 A6
	18.4 - 30	W 16 L	W 15 L	460	1545	697	4712	HD	10	TL	145 A6
	18.4 - 30	W 16 L	W 15 L	460	1545	697	4712	STD	10	TT	145 A6
	18.4 - 30	W 16 L	W 15 L	460	1545	697	4712	HD	12	TT	149 A6

STD: Standard - HD: Heavy Duty

Tolerances: O.D. ± 2% - S.W. ± 2% - RC ± 2.5% - LI/SS = Load Index / Speed Symbol; S.W. = Section Width; O.D. = Overall Diameter; SLR = Static Loaded Radius; RC = Rolling Circumference



Bias

R-1

A6

168

Technologies



Special Compound



Reinforced Carcass

Performance



Traction



High Load Capacity



Self-Cleaning



Durability



Cut and Chip Resistance



	Tire size	RIM		S.W. (mm)	O.D. (mm)	SLR (mm)	RC (mm)	Version	PR	Type	LI/SS
		Rec.	Alt.								
Ø 30"	18.4 - 30	W 16 L	W 15 L	460	1545	697	4712	STD	12	TL	149 A6
	18.4 - 30	W 16 L	W 15 L	460	1545	697	4712	STD	12	TT	149 A6
	18.4 - 30	W 16 L	W 15 L	460	1545	697	4712	STD	14	TT	151 A6
	18.4 - 30	W 16 L	W 15 L	460	1545	697	4712	STD	16	TT	154 A6
	23.1 - 30	DW 20 B ; DW 20 A	-	600	1700	773	5217	STD	8	TT	146 A6
	23.1 - 30	DW 20 B ; DW 20 A	-	600	1700	773	5217	STD	8	TL	146 A6
	23.1 - 30	DW 20 B ; DW 20 A	-	600	1700	773	5217	DB	12	TT	155 A6
	23.1 - 30	DW 20 B ; DW 20 A	-	600	1700	773	5217	STD	12	TL	155 A6
	23.1 - 30	DW 20 B ; DW 20 A	-	600	1700	773	5217	STD	12	TT	155 A6
Ø 32"	8.3 - 32	W 7	W 6	211	1195	572	3585	STD	6	TT	105 A6
	8.3 - 32	W 7	W 6	211	1195	572	3585	STD	8	TT	111 A6
	9.5 - 32	W 8	W 7	235	1255	594	3686	STD	6	TT	110 A6

STD: Standard - DB: Dual Bead

Tolerances: O.D. ± 2% - S.W. ± 2% - RC ± 2.5% - LI/SS = Load Index / Speed Symbol; S.W. = Section Width; O.D. = Overall Diameter; SLR = Static Loaded Radius; RC = Rolling Circumference



Bias



Technologies



Special Compound



Reinforced Carcass

Performance



Traction



High Load Capacity



Self-Cleaning



Durability



Cut and Chip Resistance



	Tire size	RIM		S.W. (mm)	O.D. (mm)	SLR (mm)	RC (mm)	Version	PR	Type	LI/SS
		Rec.	Alt.								
Ø 32"	11.2 - 32	W 10	W 9	287	1310	615	4007	HD	8	TL	120 A6
	12.4 - 32	W 11	W 9; W 10	325	1360	639	3998	STD	6	TT	119 A6
	12.4 - 32	W 11	W 9; W 10	325	1360	639	3998	HD	8	TT	124 A6
	12.4 - 32	W 11	W 9; W 10	325	1360	639	3998	STD	8	TT	124 A6
	12.4 - 32	W 11	W 9; W 10	325	1360	639	3998	HD	10	TT	128 A6
Ø 34"	16.9 - 34	W 15 L	W 14 L	429	1585	728	4794	HD	8	TT	139 A6
	16.9 - 34	W 15 L	W 14 L	429	1585	728	4794	STD	8	TT	139 A6
	16.9 - 34	W 15 L	W 14 L	429	1585	728	4794	HD	10	TT	142 A6
	16.9 - 34	W 15 L	W 14 L	429	1585	728	4794	STD	10	TT	142 A6
	16.9 - 34	W 15 L	W 14 L	429	1585	728	4794	HD	12	TT	144 A6
	16.9 - 34	W 15 L	W 14 L	429	1585	728	4794	STD	12	TT	144 A6
	16.9 - 34	W 15 L	W 14 L	429	1585	728	4794	HD	14	TT	142 A6
	18.4 - 34	W 16 L	W 15 L	467	1650	751	5009	STD	6	TT	137 A6
	18.4 - 34	W 16 L	W 15 L	467	1650	751	5009	HD	8	TT	142 A6

STD: Standard - HD: Heavy Duty

Tolerances: O.D. ± 2% - S.W. ± 2% - RC ± 2.5% - LI/SS = Load Index / Speed Symbol; S.W. = Section Width; O.D. = Overall Diameter; SLR = Static Loaded Radius; RC = Rolling Circumference



Bias



Technologies



Special Compound



Reinforced Carcass

Performance



Traction



High Load Capacity



Self-Cleaning



Durability



Cut and Chip Resistance



	Tire size	RIM		S.W. (mm)	O.D. (mm)	SLR (mm)	RC (mm)	Version	PR	Type	LI/SS
		Rec.	Alt.								
Ø 34"	18.4 - 34	W 16 L	W 15 L	467	1650	751	5009	STD	8	TT	142 A6
	18.4 - 34	W 16 L	W 15 L	467	1650	751	5009	HD	10	TT	146 A6
	18.4 - 34	W 16 L	W 15 L	467	1650	751	5009	STD	10	TT	146 A6
	18.4 - 34	W 16 L	W 15 L	467	1650	751	5009	HD	12	TT	151 A6
	18.4 - 34	W 16 L	W 15 L	467	1650	751	5009	HD SPL	12	TT	151 A6
	18.4 - 34	W 16 L	W 15 L	467	1650	751	5009	STD	12	TT	151 A6
	18.4 - 34	W 16 L	W 15 L	467	1650	751	5009	HD	14	TT	154 A6
	18.4 - 34	W 16 L	W 15 L	467	1650	751	5009	STD	14	TT	154 A6
	23.1 - 34	DW 20 B ; DW 20 A	-	585	1810	834	5321	STD	10	TT	153 A6
	23.1 - 34	DW 20 B ; DW 20 A	-	585	1810	834	5321	STD	10	TL	153 A6
Ø 36"	8.3 - 36	W 7	W 6	211	1295	628	4028	STD	6	TT	107 A6
	8.3 - 36	W 7	W 6	211	1295	628	4028	STD	8	TT	113 A6
	9.5 - 36	W 8	W 7	235	1360	646	4000	STD	10	TT	122 A6
	12.4 - 36	W 11	W 9 ; W 10	325	1465	696	4546	HD	8	TT	126 A6

STD: Standard - HD: Heavy Duty - HD SPL: Heavy Duty Special

Tolerances: O.D. ± 2% - S.W. ± 2% - RC ± 2.5% - LI/SS = Load Index / Speed Symbol; S.W. = Section Width; O.D. = Overall Diameter; SLR = Static Loaded Radius; RC = Rolling Circumference



Bias

R-1

A6

168

Technologies



Special Compound



Reinforced Carcass

Performance



Traction



High Load Capacity



Self-Cleaning



Durability



Cut and Chip Resistance



	Tire size	RIM		S.W. (mm)	O.D. (mm)	SLR (mm)	RC (mm)	Version	PR	Type	LI/SS
		Rec.	Alt.								
Ø 36"	12.4 - 36	W 11	W 9; W 10	325	1465	696	4546	STD	8	TT	126 A6
	12.4 - 36	W 11	W 9; W 10	325	1465	696	4546	HD	10	TT	131 A6
	12.4 - 36	W 11	W 9; W 10	325	1465	696	4546	STD	10	TT	131 A6
	12.4 - 36	W 11	W 9; W 10	325	1465	687	4558	HD	12	TT	135 A6
	12.4 - 36	W 11	W 9; W 10	325	1465	696	4546	STD	12	TT	135 A6
	12.4 - 36	W 11	W 9; W 10	325	1465	696	4546	HD	14	TL	139 A6
	12.4 - 36	W 11	W 9; W 10	325	1465	696	4546	HD	14	TT	139 A6
	12.4 - 36	W 11	W 9; W 10	325	1465	696	4546	STD	14	TT	139 A6
	13.6 - 36	W 12	W 11	345	1515	713	4687	STD	6	TT	125 A6
	13.6 - 36	W 12	W 11	345	1515	712	4687	STD	8	TT	129 A6
	13.6 - 36	W 12	W 11	345	1515	713	4687	HD	10	TT	134 A6
	13.6 - 36	W 12	W 11	345	1515	713	4687	STD	10	TT	134 A6
Ø 38"	11.2 - 38	W 10	W 9	284	1460	686	4409	STD	6	TL	117 A6
	12.4 - 38	W 11	W 9; W 10	325	1525	718	4670	STD	8	TT	127 A6

STD: Standard - HD: Heavy Duty

Tolerances: O.D. ± 2% - S.W. ± 2% - RC ± 2.5% - LI/SS = Load Index / Speed Symbol; S.W. = Section Width; O.D. = Overall Diameter; SLR = Static Loaded Radius; RC = Rolling Circumference



Bias



Technologies



Special Compound



Reinforced Carcass

Performance



Traction



High Load Capacity



Self-Cleaning



Durability



Cut and Chip Resistance



	Tire size	RIM		S.W. (mm)	O.D. (mm)	SLR (mm)	RC (mm)	Version	PR	Type	LI/SS
		Rec.	Alt.								
Ø 38"	12.4 - 38	W 11	W 9 ; W 10	325	1525	718	4670	STD	14	TT	138 A6
	12.4 - 38	W 11	W 9 ; W 10	325	1525	718	4670	STD	14	TL	138 A6
	13.6 - 38 (14.00 - 38)	W 12	W 11	345	1565	735	4832	HD	8	TT	131 A6
	13.6 - 38 (14.00 - 38)	W 12	W 11	345	1565	735	4832	STD	8	TT	131 A6
	13.6 - 38 (14.00 - 38)	W 12	W 11	345	1565	735	4832	HD	12	TT	139 A6
	13.6 - 38 (14.00 - 38)	W 12	W 11	355	1565	735	4832	STD	12	TT	139 A6
	13.6 - 38 (14.00 - 38)	W 12	W 11	345	1565	735	4832	STD	14	TT	142 A6
	14.00 - 38 (13.6 - 38)	W 12	W 11	345	1565	735	4832	STD	8	TT	131 A6
	14.00 - 38 (13.6 - 38)	W 12	W 11	345	1565	735	4832	SPL	12	TT	139 A6
	15.5 - 38	W 14 L	-	395	1585	746	4660	HD	8	TT	133 A6
	15.5 - 38	W 14 L	-	395	1585	746	4660	HD	8	TL	133 A6
	15.5 - 38	W 14 L	-	395	1585	746	4660	STD	8	TT	133 A6
	15.5 - 38	W 14 L	-	395	1585	746	4760	HD	10	TT	138 A6
	15.5 - 38	W 14 L	-	395	1585	746	4660	STD	10	TT	138 A6

STD: Standard - HD: Heavy Duty - SPL: Special

Tolerances: O.D. ± 2% - S.W. ± 2% - RC ± 2.5% - LI/SS = Load Index / Speed Symbol; S.W. = Section Width; O.D. = Overall Diameter; SLR = Static Loaded Radius; RC = Rolling Circumference



Bias



Technologies



Special Compound



Reinforced Carcass

Performance



Traction



High Load Capacity



Self-Cleaning



Durability



Cut and Chip Resistance



	Tire size	RIM		S.W. (mm)	O.D. (mm)	SLR (mm)	RC (mm)	Version	PR	Type	LI/SS
		Rec.	Alt.								
Ø 38"	15.5 - 38	W 14 L	-	395	1585	746	4660	STD	12	TT	141 A6
	16.9 - 38	W 15 L	W 14 L	429	1685	788	4954	HD	8	TT	141 A6
	16.9 - 38	W 15 L	W 14 L	429	1685	788	4954	STD	8	TT	141 A6
	16.9 - 38	W 15 L	W 14 L	429	1685	788	4954	HD	10	TT	143 A6
	16.9 - 38	W 15 L	W 14 L	429	1685	788	4954	STD	10	TT	143 A6
	16.9 - 38	W 15 L	W 14 L	429	1685	788	4954	STD	12	TT	146 A6
	18.4 - 38	W 16 L	W 15 L	467	1750	794	5366	HD	8	TT	143 A6
	18.4 - 38	W 16 L	W 15 L	467	1750	794	5366	STD	8	TT	143 A6
	18.4 - 38	W 16 L	W 15 L	467	1750	794	5366	HD	10	TT	148 A6
	18.4 - 38	W 16 L	W 15 L	467	1750	794	5366	HD	10	TL	148 A6
	18.4 - 38	W 16 L	W 15 L	467	1750	794	5366	HD	12	TT	153 A6
	18.4 - 38	W 16 L	W 15 L	467	1750	794	5366	STD	12	TT	153 A6
	18.4 - 38	W 16 L	W 15 L	467	1750	794	5366	STD	12	TL	153 A6
	18.4 - 38	W 16 L	W 15 L	467	1750	794	5366	STD	14	TT	155 A6

STD: Standard - HD: Heavy Duty

Tolerances: O.D. ± 2% - S.W. ± 2% - RC ± 2.5% - LI/SS = Load Index / Speed Symbol; S.W. = Section Width; O.D. = Overall Diameter; SLR = Static Loaded Radius; RC = Rolling Circumference



Bias



Technologies



Special Compound



Reinforced Carcass

Performance



Traction



High Load Capacity



Self-Cleaning



Durability



Cut and Chip Resistance



	Tire size	RIM		S.W. (mm)	O.D. (mm)	SLR (mm)	RC (mm)	Version	PR	Type	LI/SS
		Rec.	Alt.								
Ø 38"	20.8 - 38	W 18 L	W 16 L	530	1835	846	5684	STD	8	TT	148 A6
	20.8 - 38	W 18 L	W 16 L	530	1835	846	5684	HD	12	TT	156 A6
	20.8 - 38	W 18 L	W 16 L	530	1835	846	5684	STD	12	TT	156 A6
	20.8 - 38	W 18 L	W 16 L	530	1835	846	5684	STD	12	TL	156 A6
	20.8 - 38	W 18 L	W 16 L	530	1835	846	5684	STD	14	TT	160 A6
	20.8 - 38	W 18 L	W 16 L	530	1835	846	5684	DB HD	16	TT	163 A6
	20.8 - 38	W 18 L	W 16 L	530	1835	846	5684	DB HD	18	TT	166 A6
	20.8 - 38	W 18 L	W 16 L	530	1835	846	5684	DB HD	18	TL	166 A6
Ø 42"	9.5 - 42	W 8	W 7	246	1510	721	4663	STD	10	TT	125 A6
	12.4 - 42	W 10 ; W 10 A	-	322	1630	770	5011	STD	10	TL	134 A6
	20.8 - 42 (42)	W 18 L	W 16 L	535	1950	909	5733	STD	12	TL	158 A6
	20.8 - 42	W 18 L	W 16 L	535	1950	909	5733	STD	12	TT	158 A6
	20.8 - 42	W 18 L	W 16 L	535	1950	909	5733	STD	16	TL	165 A6
	20.8 - 42	W 18 L	W 16 L	535	1950	909	5733	DB HD	18	TL	168 A6

STD: Standard - HD: Heavy Duty - DB HD: Dual Bead Heavy Duty

Tolerances: O.D. ± 2% - S.W. ± 2% - RC ± 2.5% - LI/SS = Load Index / Speed Symbol; S.W. = Section Width; O.D. = Overall Diameter; SLR = Static Loaded Radius; RC = Rolling Circumference