



## XL GRIP (SCRAPER)

### Description

XL GRIP (SCRAPER) is a non-directional wide-base tire, particularly suitable for scrapers on any terrain. The tire features a strong casing and a special tread compound providing high cut and puncture resistance as well as excellent durability and traction even during heavy-duty operations. Additional features are best self-cleaning properties and exceptional stability.

### UM

IS Standard

### Construction

◆ Bias

### Machinery

OTR ■ Scraper



Version STANDARD

Tire Type TL

Tyre size 37.5-39

LI/SS

## Dimensions IS Standard

OD (IS) (mm)	2570
Rim Rec	32.00/4.5
TRA Code	E3

## Load Capacity (IS)

km/h / bar	4.75	6.50
50	26500	-
10	-	42500

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 28-02-2026

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..