



US standard



GROWING TOGETHER

AT 110



PRODUCT DATA SHEET



Bias



AT 110

AT 110 is BKT's tire suitable for all-terrain applications with ATVs. Thanks to its extraordinary steering control, AT 110 is the ideal front axle tire for your vehicle.

Performance



Steering Control

	US CODE	Tire size	RIM		S.W. (In.)	O.D. (In.)	SLR (In.)	RC (In.)	TREAD DEPTH (32nds)	TIRE WEIGHT (lbs)	Version	PR	Type	LI/SS
			Rec.	Alt.										
Ø 8"	94000821	AT 20 X 7 - 8	5.5 AT	6.0 AT	7.2	20.0	-	-	16	12	STD	4	TL	-
Ø 9"	94000791	AT 21 X 8 - 9	6.5 AT	6.0 AT	8.0	21.3	-	-	16	12	STD	4	TL	-
Ø 10"	94026821	AT 21 X 7 - 10	5.5 AT	6.0 AT	7.0	20.9	-	-	16	12	STD	4	TL	-
	94000807	AT 22 X 8 - 10	6.5 AT	6.0 AT	8.0	21.6	-	-	16	12	STD	4	TL	-
	94026838	AT 23 X 7 - 10	5.5 AT	6.0 AT	7.0	23.0	-	-	16	14	STD	4	TL	-

STD: Standard



Tolerances: O.D. ± 2% - S.W. ± 2% - RC ± 2.5% - LI/SS = Load Index / Speed Symbol; S.W. = Section Width; O.D. = Overall Diameter; SLR = Static Loaded Radius; RC = Rolling Circumference