



AGRIMAX SPARGO


Description

AGRIMAX SPARGO is the special BKT tire for row crop applications. It has been designed for enhanced productivity in the fields and for preserving the soil in the long term. Thanks to VF technology, the tire provides higher load capacity at standard pressure. Thanks to a strong casing and an increased number of lugs, AGRIMAX SPARGO ensures outstanding durability along with strong stability both in the fields and during road transfers.

UM

US Standard

Construction

 Radial

Machinery

Agriculture ■ Tractor



Version	STANDARD
Tire Type	TL
Tyre size	VF480/95R54
LI/SS	180;D

Dimensions US Standard

USA Code	94514953
SW (US) (in)	20.0
OD (US) (in)	90.6
SLR (US) (in)	40.7
RC (US) (in)	273.9
Rim Rec	DW 16 L
Rim Alt	DW 15 L
ECE	E11-106R-0011499
TRA Code	R1

Load Capacity (US)

mph / psi	14	17	20	23	26	29	32	35	46
45	9310	10440	11590	12720	13380	14030	14430	14840	16310
from 40 to 25	10060	11290	12530	13760	14470	15170	15610	16050	17640
20	10270	11520	12780	14040	14760	15480	15930	16380	17990
12	10470	11740	13030	14310	15050	15790	16240	16700	18350
5	11070	12430	13780	15140	15920	16690	17180	17660	19400
Upto 10 Cyc.	13630	15300	16980	18660	19600	20560	21160	21750	23900
Upto 20 Cyc.	11420	12820	14220	15620	16430	17220	17730	18230	20020

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 28-02-2026

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..