



## RIDEMAX FL 693 M



### Description

RIDEMAX FL 693 M is the ideal radial tire for those who frequently travel on the road with trailers/tank trucks. Actually designed for 75% on-the-road use, RIDEMAX FL 693 M provides excellent road performance prioritizing both comfort and self-cleaning properties. The speed index classes D/E of the range stands for higher speeds when travelling on the road leading to significant time savings.

### UM

IS Standard

### Construction

### Machinery

Agriculture ■ Tanker

Version	HD
Tire Type	TL
Tyre size	650/55R26.5
LI/SS	178;D

## Dimensions IS Standard

SW (IS) (mm)	645
OD (IS) (mm)	1389
SLR (IS) (mm)	615
RC (IS) (mm)	4250
Rim Rec	AG 20.00
ECE	E11-106R-003008

## field\_1

km/h / bar	1.0	1.2	1.6	2.0	2.4	2.8	3.2	3.6	4.0	5.0	6.0
65	2325	2775	3375	3900	4500	5100	5475	6075	6675	7050	750
50	2815	3360	4085	4720	5445	6175	6625	7355	8080	8535	907
40	3165	3775	4590	5305	6120	6940	7450	8265	9080	9590	102
30	3515	4195	5100	5890	6795	7705	8270	9175	10080	10650	113
25	3675	4385	5335	6165	7110	8060	8655	9600	10550	11140	118
10	4185	4995	6075	7020	8100	9180	9855	10935	12015	12690	135

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 25-02-2026

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..