



MULTIMAX MT 518



Description

MULTIMAX MT 518 has been specially designed for military trucks. It is a block pattern and steel-belted tire featuring high puncture resistance as well as outstanding stability. Besides, MULTIMAX MT 518 withstands high speed and provides an extended tire life-cycle.

UM

IS Standard

Construction

 Radial

Machinery

Industrial & Construction ■

Version	STANDARD
Tire Type	TL
Tyre size	36x12.5R16.5
LI/SS	129;N

Dimensions IS Standard

SW (IS) (mm)	315
OD (IS) (mm)	902
SLR (IS) (mm)	420
RC (IS) (mm)	2758
Rim Rec	9.75
ECE	E11-54R-0017917

Load Capacity (IS)

km/h / bar	4.5
140	1850

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 28-02-2026

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..