



RIDEMAX IT 696



Description

RIDEMAX IT 696 has a unique tread design and a wide footprint that provides excellent grip for road applications, even in winter conditions. The tire is best suitable for transport and municipality/maintenance applications thanks to its high-speed feature and strong casing. The tread design has been specifically developed for heavy-duty services and ensures a low rolling resistance that provides fuel economy plus great stability.

UM

IS Standard

Construction

 Radial

Machinery

Agriculture ■ Tractor

Version	STANDARD
Tire Type	TL
Tyre size	360/80R24IND
LI/SS	143;A8

Dimensions IS Standard

SW (IS) (mm)	343
OD (IS) (mm)	1186
SLR (IS) (mm)	537
RC (IS) (mm)	3556
Rim Rec	DW 11
Rim Alt	W 12; W 10
ECE	E11-106R-004753

Load Capacity (IS)

km/h / bar	1.2	1.6	2.0	2.4	2.8	3.2
65	1110	1370	1605	1865	2100	2360
50	1200	1480	1735	2015	2270	2550
40	1280	1580	1855	2155	2425	2725
30	1535	1895	2225	2585	2910	3270

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 28-02-2026

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..