



AGRIMAX PROCROP



Description

AGRIMAX PROCROP is precisely engineered for farming demand in row crop and spraying applications. It features advanced VF (Very High Flexion) technology, allowing PROCROP to carry 40% more load compared to standard tires at the same tire pressure. At the same time, the wide footprint of AGRIMAX PROCROP ensures low soil compaction and even weight distribution that avoids damage to crops.

UM

IS Standard

Construction

 Radial

Machinery

Agriculture ■ Sprayer

Version	STEEL BELTED
Tire Type	TL
Tyre size	VF230/95R48
LI/SS	148;D

Dimensions IS Standard

SW (IS) (mm)	233
OD (IS) (mm)	1660
SLR (IS) (mm)	785
RC (IS) (mm)	5100
Rim Rec	W8
Rim Alt	W7
ECE	E11-106R-0011158

Load Capacity (IS)

km/h / bar	1.0	1.2	1.4	1.6	2.0	2.4	2.8	3.2	3.6	4.0				
70	1350	1525	1695	1840	2040	2155	2355	2555	2730	2870				
from 65 to 40	1485	1670	1860	2020	2240	2365	2585	2805	2995	3150				
30	1515	1705	1900	2060	2285	2415	2640	2865	3055	3215				
20	1545	1740	1940	2100	2330	2460	2690	2920	3120	3280				
10	1630	1840	2045	2220	2465	2600	2845	3085	3295	3465				
Upto 15 Cyc.	2010	2265	2520	2735	3035	3205	3505	3805	4060	4270				
Upto 30 Cyc.	1685	1900	2115	2295	2545	2685	2940	3190	3405	3580				

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different L condition.

Printed on 24-02-2026

All product data contained in this publication are for information purposes only and may be modified at any time without notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for errors or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without the written consent by Balkrishna Industries Ltd..