



FLOTATION 648



Description

FLOTATION 648 is particularly suitable for field and road transport as well as for spreading operations. Some sizes are designed for hay harvesters/balers. The special tread design allows for carrying very heavy loads at low pressure, guaranteeing at the same time reduced soil compaction and preventing damage to crops.

UM

IS Standard

Construction

◆ Bias

Machinery

Agriculture ■ Baler

Version	STANDARD
Tire Type	TL
Tyre size	550/45-22.5
LI/SS	

Dimensions IS Standard

SW (mm)	525
OD (mm)	1070
SLR (mm)	488
RC (mm)	3253
Rim Rec	AG 16.00
ECE	E4-106R-002309

Load Capacity (IS)

km/h / bar	2.40	2.60	2.80
10 FR	5600	5865	6125
20 FR	5040	5280	5515
30 FR	4480	4695	4900
40 FR	4000	4190	4375
50 FR	3600	3770	4000
10 DW	3935	4125	4305
20 DW	3540	3710	3875
30 DW	3145	3300	3445
40 DW	2810	2945	3075
50 DW	2530	2650	2800

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 21-03-2026

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..