



US standard



GROWING TOGETHER

AW 726



PRODUCT DATA SHEET



Bias



149

Technologies



Block Pattern

Performance



Durability



Self-Cleaning



AW 726

AW 726 has been specially designed for trailers in transport operations. It is best suited for both on-and-off-the-road usage. AW 726 shows excellent road performance and self-cleaning features. The block pattern design provides an extended tire life-cycle.

	US CODE	Tire size	RIM		S.W. (In.)	O.D. (In.)	SLR (In.)	RC (In.)	TREAD DEPTH (32nds)	TIRE WEIGHT (lbs)	Version	PR	Type	LI/SS	
			Rec.	Alt.										DW	FR
Ø 15.3"	94064366	11.5/80 - 15.3	9.00	-	11.8	33.7	14.3	99.6	14	55	AB	14	TL	126 A8	139 A8
	94053698	11.5/80 - 15.3	9.00	-	11.8	33.7	14.3	99.6	14	53	STD	14	TL	126 A8	139 A8
	94067695	11.5/80 - 15.3	9.00	-	11.8	33.7	14.7	100.0	14	61	SB	14	TL	126 A8	139 A8
Ø 15.5"	94054008	400/60 - 15.5	AG 13.00	-	15.7	34.4	-	-	17	88	STD	18	TL	137 A8	149 A8
Ø 17"	94055647	420/55 - 17	13.00	-	16.3	35.0	15.4	101.7	17	88	STD	-	TL	121 A8	133 A8

AB: Aramid Belted - STD: Standard - SB: Steel Belted



Tolerances: O.D. ± 2% - S.W. ± 2% - RC ± 2.5% - LI/SS = Load Index / Speed Symbol; S.W. = Section Width; O.D. = Overall Diameter; SLR = Static Loaded Radius; RC = Rolling Circumference; DW = Drive Wheel; FR = Free Rolling