



## AW 702

### Description

AW 702 has been developed for implement machinery, trailers and balers in soil tillage and haulage applications. This heavy-duty tire has been designed by BKT to provide a new level of durability. AW 702 is available in different versions to meet specific end-user needs: an "aramid belted" version for those who need strengthened puncture resistance, the "HD" version has a special cut-and-chip resistant compound, while the "special" version provides extraordinary stubble resistance.



### UM

US Standard

### Construction

 Bias

### Machinery

Agriculture ■ Baler, Industrial & Construction ■ Trailer

Version	STANDARD
Tire Type	TL
Tyre size	10.5/80-18
LI/SS	

## Dimensions US Standard

USA Code	94009343
SW (US) (in)	10.8
OD (US) (in)	34.8
SLR (US) (in)	15.6
RC (US) (in)	102.1
Rim Rec	W 9
Rim Alt	W 8; 9
ECE	E11-106R-003577

## Load Capacity (US)

mph / psi	74
5 FR	7290
15 FR	6190
20 FR	5830
25 FR	5200

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 28-02-2026

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..