



US standard



GROWING TOGETHER

FARM HIGHWAY TOUGH



PRODUCT DATA SHEET



Bias



Technologies



High Speed

Performance



Durability



High Load Capacity



FARM HIGHWAY TOUGH

FARM HIGHWAY TOUGH is a high-speed tire designed for transport and soil tillage applications with trailers and implement machinery. It provides high load capacity also at high speeds and ensures a long tire life-cycle.

	US CODE	Tire size	RIM		S.W. (In.)	O.D. (In.)	SLR (In.)	RC (In.)	TREAD DEPTH (32nds)	TIRE WEIGHT (lbs)	Version	PR	Type	LI/SS
			Rec.	Alt.										
Ø 15"	94037605	9.5 L - 15 FI	7.00	8 LB	9.6	30.2	13.5	85.9	11	47	STD	12	TL	-
	94039920	9.5 L - 15 FI	7.00	8 LB	9.6	30.2	13.5	85.9	11	42	STD	8	TL	-
	94044733	10.00 - 15 FI	8 LB	-	10.8	33.6	-	-	12	56	STD	8	TL	128 J
	94032518	11 L - 15 FI	8 LB	10 LB ; 8 J	11.0	30.6	13.7	87.2	12	51	STD	12	TL	128 J
	94039937	11 L - 15 FI	8 LB	10 LB ; 8 J	11.0	30.6	13.7	87.2	12	45	STD	8	TL	120 J
	94032525	12.5 L - 15 FI	10 LB	-	12.5	32.1	14.3	91.5	12	66	STD	12	TL	134 J

STD: Standard



Tolerances: O.D. ± 2% - S.W. ± 2% - RC ± 2.5% - LI/SS = Load Index / Speed Symbol; S.W. = Section Width; O.D. = Overall Diameter; SLR = Static Loaded Radius; RC = Rolling Circumference



GROWING TOGETHER

All images, texts and graphics contained in this brochure are the copyright of BKT. Permission is granted to print hard copies of this material. Any other form of reproduction, electronic or otherwise, as well as the application of any changes, partially or entirely, to images, texts, graphs and data is strictly prohibited without prior written permission by BKT. Balkrishna Industries Limited (BKT) reserves itself the right to alter any details contained in the publication without prior notice. EN-US / 08-2024