



US standard



GROWING TOGETHER

SKID POWER HD (A)



PRODUCT DATA SHEET



Bias



152



SKID POWER HD (A)

SKID POWER HD (A) has been designed for skid steers in construction applications. The tire features an extra deep tread and sidewall protection providing excellent cut and chip resistance and outstanding durability. SKID POWER HD (A) is the ideal tire for loose surfaces and heavy-duty service.

Performance



Cut and Chip Resistance



Durability



Heavy Duty



Self-Cleaning



Traction on Sand



For muddy ground

	US CODE	Tire size	Type	PR	LI/SS	Version	O.D.	S.W.	SLR	RC	TREAD DEPTH (32nds)	TIRE WEIGHT (lbs)	RIM	
							(In.)	(In.)	(In.)	(In.)			Rec.	Alt.
Ø 8"	94030422	18 X 8.5 - 8	TL	8	97A2	STD	18.1	8.3	8.1	53.4	17	18	7.00 I - 55 ; I - 70 ; I - 90	-
Ø 12"	94056095	23 X 8.5 - 12	TL	6	87A8	IMP	23.0	8.5	10.7	69.4	18	26	7.00 I - 55	7.00 I - 70 ; 7 JA
	94017775	23 X 8.5 - 12	TL	6	-	STD	23.0	8.5	10.7	69.4	18	26	7.00 I - 55	7.00 I - 70 ; 7 JA
	94017805	23 X 8.5 - 12	TL	8	-	STD	23.0	8.5	10.7	69.4	18	26	7.00 I - 55	7.00 I - 70 ; 7 JA
	94056101	23 X 8.5 - 12	TL	12	98A8	IMP	23.0	8.5	10.7	69.4	18	29	7.00 I - 55	7.00 I - 70 ; 7 JA
	94017812	23 X 8.5 - 12	TL	12	-	STD	23.0	8.5	10.7	69.4	18	29	7.00 I - 55	7.00 I - 70 ; 7 JA
	94017836	26 X 12 - 12	TL	8	-	STD	26.0	12.0	11.7	76.7	30	46	10.50 I - 55	8.50 I - 55 ; 10.50 I - 70 ; 8½ JA ; 9½ JA ; 10½ JA
	94017843	26 X 12 - 12	TL	10	-	STD	26.0	12.0	11.7	76.7	30	46	10.50 I - 55	8.50 I - 55 ; 10.50 I - 70 ; 8½ JA ; 9½ JA ; 10½ JA
	94056019	26 X 12 - 12	TL	12	114A8	IMP	26.0	12.0	11.7	76.7	30	46	10.50 I - 55	8.50 I - 55 ; 10.50 I - 70 ; 8½ JA ; 9½ JA ; 10½ JA
	94017850	26 X 12 - 12	TL	12	-	STD	26.0	12.0	12.1	78.3	30	46	10.50 I - 55	8.50 I - 55 ; 10.50 I - 70 ; 8½ JA ; 9½ JA ; 10½ JA
	94026203	27 X 10 - 12 (250/75 - 12)	TT	14	152A2	IND	27.6	10.0	-	-	23	53	8.00 G	-

STD: Standard - IMP: Implement - IND: Industrial

Tolerances: O.D. ± 2% - S.W. ± 2% - RC ± 2.5% - LI/SS = Load Index / Speed Symbol; S.W. = Section Width; O.D. = Overall Diameter; SLR = Static Loaded Radius; RC = Rolling Circumference



Bias



Performance



Cut and Chip Resistance



Durability



Heavy Duty



Self-Cleaning



Traction on Sand



For muddy ground

	US CODE	Tire size	Type	PR	LI/SS	Version	O.D.	S.W.	SLR	RC	TREAD DEPTH (32nds)	TIRE WEIGHT (lbs)	RIM	
							(In.)	(In.)	(In.)	(In.)			Rec.	Alt.
Ø 15"	94056033	27 X 8.5 - 15	TL	8	102 A8	IMP	26.6	8.6	12.8	78.9	18	35	7 JA	-
	94017881	27 X 8.5 - 15	TL	8	-	STD	26.6	8.6	12.8	78.9	18	35	7 JA	-
	94056026	27 X 10.5 - 15	TL	8	105 A8	IMP	26.9	10.1	12.8	80.2	18	43	8 LB	-
	94017867	27 X 10.5 - 15	TL	8	-	STD	26.9	10.1	12.8	80.2	18	43	8 LB	-
	94057528	27 X 10.5 - 15	TL	8	105 A8	TRTR	26.9	10.1	12.8	80.2	18	43	8 LB	-
	94017911	31 X 15.5 - 15	TL	8	-	STD	31.1	15.9	14.9	94.9	26	82	13 LB	-
	94056057	31 X 15.5 - 15	TL	10	125 A8	IMP	31.1	15.9	14.9	94.9	26	82	13 LB	-
	94065226	31 X 15.5 - 15	TL	10	139 A2/ 121 B	STD	31.1	15.9	14.9	94.9	26	82	13 LB	-
	94075904	380/50 - 15	TL	8	-	STD	30.3	14.8	14.4	88.2	29	75	13 LB	-
Ø 16.5"	94055685	10 - 16.5	TL	8	116 A8	IMP	30.7	10.5	14.3	92.5	24	53	8.25	-
	94017614	10 - 16.5	TL	8	-	STD	30.7	10.5	14.3	92.5	24	55	8.25	-

IMP: Implement - STD: Standard - TR TR: Tractor Trailer

Tolerances: O.D. ± 2% - S.W. ± 2% - RC ± 2.5% - LI/SS = Load Index / Speed Symbol; S.W. = Section Width; O.D. = Overall Diameter; SLR = Static Loaded Radius; RC = Rolling Circumference



Bias



Performance



Cut and Chip Resistance



Durability



Heavy Duty



Self-Cleaning



Traction on Sand



For muddy ground

	US CODE	Tire size	Type	PR	LI/SS	Version	O.D.	S.W.	SLR	RC	TREAD DEPTH (32nds)	TIRE WEIGHT (lbs)	RIM	
							(In.)	(In.)	(In.)	(In.)			Rec.	Alt.
Ø 16.5"	94017645	10 - 16.5	TL	10	-	STD	30.7	10.5	14.3	92.5	24	55	8.25	-
	94055692	12 - 16.5	TL	10	125 A8	IMP	33.5	12.8	15.3	101.2	27	77	9.75	-
	94017676	12 - 16.5	TL	10	-	STD	33.5	12.8	15.3	101.2	27	77	9.75	-
	94055739	12 - 16.5	TL	12	130 A8	IMP	33.5	12.8	15.3	101.2	27	79	9.75	-
	94017706	12 - 16.5	TL	12	145 A2	STD	33.5	12.8	15.3	101.2	27	79	10.15	-
	94069484	12 - 16.5	TL	14	-	STD	33.5	12.8	15.3	101.2	27	82	9.75	-
	94056064	31.5 X 13 - 16.5	TL	10	124 A8	IMP	31.3	13.0	14.3	92.3	24	67	9.75	-
	94017904	31.5 X 13 - 16.5	TL	10	-	STD	31.3	13.0	14.3	92.3	24	67	9.75	-
	94057245	33 X 15.5 - 16.5	TL	12	131 A8	IMP	33.0	15.5	15.2	100.9	27	98	13.00	-
	94017942	33 X 15.5 - 16.5	TL	12	148 A2	STD	33.0	15.5	15.2	100.9	27	97	13.00	-
	94060825	33 X 15.5 - 16.5	TL	14	151 A2	STD	33.0	15.5	15.2	100.9	27	99	13.00	-

IMP: Implement - STD: Standard

Tolerances: O.D. ± 2% - S.W. ± 2% - RC ± 2.5% - LI/SS = Load Index / Speed Symbol; S.W. = Section Width; O.D. = Overall Diameter; SLR = Static Loaded Radius; RC = Rolling Circumference



Bias



Performance



Cut and Chip Resistance



Durability



Heavy Duty



Self-Cleaning



Traction on Sand



For muddy ground



	US CODE	Tire size	Type	PR	LI/SS	Version	O.D. (In.)	S.W. (In.)	SLR (In.)	RC (In.)	TREAD DEPTH (32nds)	TIRE WEIGHT (lbs)	RIM	
													Rec.	Alt.
Ø 16.5"	94052219	260/70 - 16.5 (10 - 16.5)	TL	10	120 A8	IMP	30.5	10.5	14.0	90.4	24	54	8.25	-
	94017720	14 - 17.5	TL	14	-	STD	36.6	13.8	16.5	108.0	35	123	10.50	-
Ø 17.5"	94056071	14 - 17.5	TL	14	140 A8	IMP	36.6	13.8	16.5	108.0	35	122	10.50	-
	94017720	14 - 17.5	TL	14	-	STD	36.6	13.8	16.5	108.0	35	123	10.50	-
Ø 19.5"	94056088	15 - 19.5	TL	14	146 A8	IMP	40.1	15.7	18.2	121.1	35	143	11.75	12.25
	94017744	15 - 19.5	TL	14	-	STD	40.1	15.7	18.2	121.1	35	144	11.75	12.25

IMP: Implement - STD: Standard



Tolerances: O.D. ± 2% - S.W. ± 2% - RC ± 2.5% - LI/SS = Load Index / Speed Symbol; S.W. = Section Width; O.D. = Overall Diameter; SLR = Static Loaded Radius; RC = Rolling Circumference