



IS standard



GROWING TOGETHER

EARTHMAX

RADIAL OTR TIRES

SR 50



PRODUCT DATA SHEET



Radial

L-5

A2

216

Technologies



Extra Deep Tread

Performance



Traction



Cut Resistance



Stability



Durability



EARTHMAX SR 50

RADIAL OTR TIRES

EARTHMAX SR 50 (L-5) is an *All Steel* radial tire specially designed for loaders. The durable casing and sidewall protectors are ideal for the most demanding operations. EARTHMAX SR 50 is made of a special cut-resistant compound which ensures a long wear life. Operators will also appreciate its excellent traction, stability and comfortable ride.

	Tire size	Type	TRA CODE	STAR RATING	LI/SS	Version	TKPH	O.W.	O.D.	SLR	RC	TREAD DEPTH (mm)	RIM	
								(mm)	(mm)	(mm)	(mm)		Rec.	Alt.
Ø 25"	26.5 R 25	TL	L-5	*	202 A2	CRC	-	690	1772	806	5334	89	22.00/3.0	-
	26.5 R 25	TL	L-5	**	209 A2	CRC	-	690	1772	806	5334	89	22.00/3.0	-
	29.5 R 25	TL	L-5	*	208 A2	CRC	-	775	1901	862	5722	96	25.00/3.5	-
	29.5 R 25	TL	L-5	**	216 A2	CRC	-	775	1901	862	5722	96	25.00/3.5	-

CRC: Cut Resistance Compound



Tolerances: O.D. ± 2% - O.W. ± 2% - RC ± 2.5% - LI/SS = Load Index / Speed Symbol; O.W. = Overall Width; O.D. = Overall Diameter; SLR = Static Loaded Radius; RC = Rolling Circumference

