



## TR 117

### Description

TR 117 is ideal for irrigation applications with pivot irrigators. Its specially designed tread pattern provides excellent traction and outstanding self-cleaning properties.

### UM

US Standard

### Construction

 Bias

### Machinery

Agriculture ■ Pivot Irrigator



Version	STANDARD
Tire Type	TL
Tyre size	11.2-24
LI/SS	106;A8

## Dimensions US Standard

USA Code	94029082
SW (US) (in)	11.2
OD (US) (in)	42.9
SLR (US) (in)	20.0
RC (US) (in)	126.2
Rim Rec	W 10
Rim Alt	W 9
ECE	E4-106R-001967
TRA Code	R1

## Load Capacity (US)

mph / psi	26	34
25	2090	---
CREEP	---	4420

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 28-02-2026

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..