



US standard



GROWING TOGETHER

BK 823



PRODUCT DATA SHEET



Bias



127



BK 823

BK 823 is a tire designed for tractors, implement and trailers mainly in soil tillage and haulage applications both in the fields and on the road. Its special block pattern makes the tire particularly suitable for heavy-duty service where excellent steering performance is required. An HD version is also available with improved cut and chip resistance.

Technologies



Block Pattern

Performance



Cut and Chip Resistance



Heavy Duty



Steering Control

	US CODE	Tire size	RIM		S.W. (In.)	O.D. (In.)	SLR (In.)	RC (In.)	TREAD DEPTH (32nds)	TIRE WEIGHT (lbs)	Version	PR	Type	LI/SS
			Rec.	Alt.										
Ø 16"	94049202	9.00 - 16	6.5	-	9.6	35.1	15.5	101.7	27	62	HD	14	TT	127 A8
	94042432	9.00 - 16	6.5	-	9.6	35.1	15.5	101.7	27	62	STD	12	TT	124 A8
	94040131	9.00 - 16	6.5	-	9.6	35.1	15.5	101.7	27	62	STD	14	TT	127 A8
	94060252	9.00 - 16	6.5	-	9.6	35.1	15.5	101.7	27	59	STD	10	TL	121 A8

HD: Heavy Duty - STD: Standard



Tolerances: O.D. ± 2% - S.W. ± 2% - RC ± 2.5% - LI/SS = Load Index / Speed Symbol; S.W. = Section Width; O.D. = Overall Diameter; SLR = Static Loaded Radius; RC = Rolling Circumference