



## MP 567

### Description

MP 567 is an agro-industrial tire suitable for field and road transport and municipality/ maintenance operations. It is the perfect tire for telehandlers and implement machinery. The MP 567 tire provides good traction in all the weather conditions as well as excellent self-cleaning properties. This tire ensures a comfortable driving experience, together with a longer service life.



### UM

IS Standard

### Construction

◆ Bias

### Machinery

Agriculture ▪ Implement Machinery, Industrial & Construction ▪ Telehandler

Version	IMPLEMENT
Tire Type	TL
Tyre size	10.0/75-15.3
LI/SS	

## Dimensions IS Standard

SW (IS) (mm)	258
OD (IS) (mm)	774
SLR (IS) (mm)	365
RC (IS) (mm)	2401
Rim Rec	9.0
ECE	E11-106R-003607

## Load Capacity (IS)

km/h / bar	7.10
40 FR	2180
40 DW	1550

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 28-02-2026

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..