



IS standard



GROWING TOGETHER

ARROW



PRODUCT DATA SHEET



Bias



ARROW

ARROW is suitable for transport applications with trailers. It is a road-oriented tire that provides a better mileage and a longer service life. ARROW has a high load capacity also at high speeds. An HD version made of a special compound is also available for users that require advanced performance.

Technologies



High Speed



Special Compound

Performance



Durability



High Load Capacity



High Mileage

| | Tire size | RIM | | S.W. (mm) | O.D. (mm) | SLR (mm) | RC (mm) | Version | PR | Type | LI/SS |
|-------|--------------|--------|-----------|--------------|--------------|-------------|------------|---------|----|------|-------|
| | | Rec. | Alt. | | | | | | | | |
| Ø 14" | 6.50 - 14 | 4.5 J | - | 175 | 695 | - | - | STD | 10 | TT | - |
| | 6.50 - 14 LT | 4.5 J | - | 175 | 695 | - | - | HD | 10 | TT | - |
| Ø 16" | 7.50 - 16 | 6.00 G | 5.50 F | 216 | 825 | - | - | STD | 12 | TT | - |
| | 7.50 - 16 | 6.00 G | 5.50 F | 216 | 825 | - | - | STD | 14 | TT | - |
| | 7.50 - 16 | 6.00 G | 5.50 F | 216 | 825 | - | - | STD | 16 | TT | - |
| Ø 20" | 9.00 - 20 | 7.0 | 6.5 ; 7.5 | 270 | 1040 | - | - | STD | 14 | TT | - |
| | 9.00 - 20 | 7.0 | 6.5 ; 7.5 | 270 | 1040 | - | - | STD | 16 | TT | - |
| | 9.00 - 20 | 7.0 | 6.5 ; 7.5 | 270 | 1040 | - | - | TRTR | 16 | TT | - |
| | 10.00 - 20 | 7.5 | 7.0 ; 8.0 | 286 | 1075 | - | - | STD | 16 | TT | - |

STD: Standard - HD: Heavy Duty - TR TR: Tractor Trailer



Tolerances: O.D. ± 2% - S.W. ± 2% - RC ± 2.5% - LI/SS = Load Index / Speed Symbol; S.W. = Section Width; O.D. = Overall Diameter; SLR = Static Loaded Radius; RC = Rolling Circumference