



US standard



GROWING TOGETHER

MAGLIFT EXCAVATOR



PRODUCT DATA SHEET



Solid



MAGLIFT EXCAVATOR

MAGLIFT EXCAVATOR has been specifically designed for wheeled excavators in digging, loading and road construction operations. The tire is made of a special tread compound, which ensures excellent cut and chip resistance and an extended tire life-cycle. The aggressive tread design provides a high level of handling comfort combined with excellent lateral traction even under heavy-duty service conditions in addition to top self-cleaning properties. Its reinforced bead structure ensures best grip and eliminates any slippage risk during operations, whilst the special bead shape simplifies mounting operations on the rim. MAGLIFT EXCAVATOR is a puncture-and-maintenance-free tire operators can rely on.

Technologies



Special Compound



Reinforced Bead

Performance



Cut and Chip Resistance



Durability



Handling and Comfort



Traction



Self-Cleaning

	US CODE	Tire size	Type	PR	LI/SS	Version	O.D. (In.)	O.W. (In.)	SLR (In.)	RC (In.)	TREAD DEPTH (32nds)	TIRE WEIGHT (lbs)	RIM	
													Rec.	Alt.
Ø 20"	94071180	10.00 - 20	-	-	-	STD	39.8	9.4	-	-	90	312	7.00 - 20	-
	94071197	10.00 - 20	-	-	-	STD	39.8	9.4	-	-	90	313	7.50 - 20	-
	94071203	10.00 - 20	-	-	-	STD	39.8	9.7	-	-	90	317	8.00 - 20	-
	94071173	12.00 - 20	-	-	-	STD	43.3	10.0	-	-	106	424	8.00 - 20	-
	94071111	12.00 - 20	-	-	-	STD	43.3	10.4	-	-	106	429	8.50 - 20	-

STD: Standard



Tolerances: O.D. ± 2% - O.W. ± 2% - RC ± 2.5% - LI/SS = Load Index / Speed Symbol; O.W. = Overall Width; O.D. = Overall Diameter; SLR = Static Loaded Radius; RC = Rolling Circumference