



TR 393 (B)

Description

TR 393 (B) has been specially designed for seeders, spreaders and implement machinery on and off the road. The special tread design provides best flotation and self-cleaning properties in addition to a long service life. Thanks to its large contact area, TR 393 (B) ensures excellent traction and minimizes soil compaction.

UM

IS Standard

Construction

 Bias

Machinery

Agriculture ■ Baler



Version STUBBLE RESISTANT

Tire Type TL

Tyre size 31x13.50-15

LI/SS 124;B

Dimensions IS Standard

SW (IS) (mm)	350
OD (IS) (mm)	777
Rim Rec	10 LB
ECE	E11-106R-008131
TRA Code	R3

Load Capacity (IS)

km/h / bar	5.20
50	1600

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 28-02-2026

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..