



US standard



GROWING TOGETHER

EARTHMAX

RADIAL OTR TIRES

SR 32



PRODUCT DATA SHEET



Radial

E-3

B

225

Technologies



All Steel

Performance



Traction



Cut Resistance



Durability



EARTHMAX SR 32

RADIAL OTR TIRES

EARTHMAX SR 32 is a non-directional wide-base radial tire particularly suitable for scrapers. The tire features a strong All Steel casing and a special tread compound providing excellent cut and puncture resistance as well as durability. Additional traits are exceptional traction and flotation even during heavy-duty operations.

	US CODE	Tire size	Type	STAR RATING	LI/SS	Version	TRA CODE	TMPH	O.D.	O.W.	SLR	RC	TREAD DEPTH (32nds)	TIRE WEIGHT (lbs)	RIM	
									(In.)	(In.)	(In.)	(In.)			Rec.	Alt.
Ø 29"	94066216	29.5 R 29	TL	**	202 B	CRC	E-3	197	78.0	30.1	34.8	236.6	60	1496	25.00/3.5	24.00/3.5
	94057986	33.25 R 29	TL	**	209 B	CRC	E-3	237	81.9	33.3	36.0	246.1	68	1822	27.00/3.5	26.00/3.5
Ø 35"	94064243	37.25 R 35	TL	**	218 B	CRC	E-3	310	93.7	37.9	41.8	284.6	74	2650	31.00/4.0	-
Ø 39"	94066506	40.5/75 R 39	TL	**	225 B	CRC	E-3	346	102.8	38.8	45.8	312.0	74	3484	32.00/4.5	-
	94069392	40.5/75 R 39	TL	**	225 B	STD	E-3	472	102.8	38.8	45.8	312.0	74	3470	32.00/4.5	-

CRC: Cut Resistance Compound - STD: Standard



Tolerances: O.D. ± 2% - O.W. ± 2% - RC ± 2.5% - LI/SS = Load Index / Speed Symbol; O.W. = Overall Width; O.D. = Overall Diameter; SLR = Static Loaded Radius; RC = Rolling Circumference