



EARTHMAX SR 34



Description

EARTHMAX SR 34 is an All Steel radial tire specially engineered and designed for rigid dump trucks working in several operations like mining, quarry, logging and haulage. The non-directional block tread pattern provides excellent traction and stability on any type of terrain. The strong All Steel casing features excellent wear and resistance to any snag and punctures. Its also contributes to an extended tire life-cycle even under the most heavy-duty service condition

UM

US Standard

Construction

 Radial

Machinery

OTR ■ Rigid Dump Truck

Version	ULTRA CUT RESISTANT COMPOUND
Tire Type	TL
Tyre size	16.00R25
LI/SS	183;B

Dimensions US Standard

USA Code	94076109
OD (US) (in)	59.4
SLR (US) (in)	27.3
RC (US) (in)	180.1
Rim Rec	11.25/2.0
TRA Code	E3+

Load Capacity (US)

mph / psi	109	116	123	131
30	16500	17600	18200	19300

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 28-02-2026

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..