



IS standard



GROWING TOGETHER

MT 612



PRODUCT DATA SHEET



Bias



MT 612

MT 612 has been specially designed for multipurpose use on and off the road. Its strong casing allows carrying heavy loads at high speed whereas its broad lugs provide outstanding traction. The extra tread width ensures excellent flotation on sand and mud.

Performance



Durability



For muddy ground



Traction

| | Tire size | RIM | | S.W. (mm) | O.D. (mm) | SLR (mm) | RC (mm) | Version | PR | Type | LI/SS |
|-------|--------------|---------|------|--------------|--------------|-------------|------------|---------|----|------|-------|
| | | Rec. | Alt. | | | | | | | | |
| Ø 20" | 14.00 - 20 | 10 | - | 390 | 1265 | 594 | 3827 | STD | 18 | TT | - |
| | 14.00 - 20 | 10 | - | 390 | 1265 | 594 | 3827 | STD | 20 | TT | - |
| | 14.00 - 20 | 10 | - | 390 | 1265 | 594 | 3827 | STD | 22 | TT | - |
| | 16.0/70 - 20 | 13.00 T | - | 405 | 1095 | 520 | 3327 | STD | 16 | TT | - |

STD: Standard



Tolerances: O.D. ± 2% - S.W. ± 2% - RC ± 2.5% - LI/SS = Load Index / Speed Symbol; S.W. = Section Width; O.D. = Overall Diameter; SLR = Static Loaded Radius; RC = Rolling Circumference