



US standard



GROWING TOGETHER

# EM 936



PRODUCT DATA SHEET



Bias



# EM 936

EM 936 has been specially designed for excavators and telehandlers in digging and loading operations. Besides, one size is particularly suitable for graders and loaders in grading, loading and transport applications. EM 936 features outstanding riding comfort and enhanced self-cleaning properties. It also ensures a high level of handling comfort and provides excellent traction even under heavy-duty service conditions. Its "special" version is made of a special compound.

### Performance



Comfort



Handling and Comfort



Heavy Duty



Self-Cleaning



Traction

	US CODE	Tire size	Type	PR	LI/SS	Version	O.D.	O.W.	SLR	RC	TREAD DEPTH (32nds)	TIRE WEIGHT (lbs)	RIM	
							(In.)	(In.)	(In.)	(In.)			Rec.	Alt.
Ø 15"	94074617	28 X 9.00 - 15	TL	6	102 A6	STD	29.5	9.3	-	-	-	377	7.00 I	6.5 K
	Ø 20"	94005314	10.00 - 20	TT	16	146 B	STD	41.3	10.8	19.6	125.2	25	106	7.5
	94032891	10.00 - 20	TT	16	146 B	SPL	41.3	10.8	19.6	125.2	25	106	7.5	7.0; 8.0
	94026272	11.00 - 20	TT	16	149 B	STD	43.7	11.8	20.0	130.0	31	121	8.0	7.5; 8.5
	94059645	12.5 - 20	TT	12	-	STD	40.7	13.0	18.3	126.4	26	948	11.0	-
	94005345	16.0/70 - 20 (400/70 - 20)	TL	14	149 B/ 166 A2	STD	42.9	15.9	18.9	129.7	30	128	13 SDC	13
	94039616	16.0/70 - 20 (400/70 - 20)	TT	14	149 B/ 166 A2	SPL	42.9	15.9	18.9	129.7	30	127	13 SDC	13
	94049325	16.0/70 - 20 (400/70 - 20)	TL	14	149 B/ 166 A2	SPL	42.9	15.9	18.9	129.7	30	130	13 SDC	13
	94056972	16.0/70 - 20 (400/70 - 20)	TL	16	152 B/ 168 A2	SPL	42.9	15.9	18.9	129.7	30	132	13 SDC	13
	94005383	8.25 - 20	TT	14	133 B	STD	38.6	9.3	18.4	116.9	23	75	6.5	6.0; 7.0
	94005406	9.00 - 20	TT	14	140 B	STD	39.8	10.1	18.9	120.9	25	97	7.0	6.5; 7.5
	94032884	9.00 - 20	TT	14	140 B	SPL	39.8	10.1	18.9	120.9	25	97	7.0	6.5; 7.5
Ø 24"	94005352	16.0/70 - 24 (405/70 - 24)	TL	10	143 B/ 162 A2	STD	46.1	15.9	22.6	141.7	37	157	13 SDC	13 (DC)
	94005369	16.0/70 - 24 (405/70 - 24)	TL	14	152 B/ 169 A2	STD	46.1	15.9	22.6	141.7	37	168	13 SDC	13 (DC)
	94026210	20 - 24 (22/70 - 24)	TL	12	158 B/ 173 A2	STD	54.7	21.1	26.2	165.6	37	314	16.00 T SDC	-
Ø 25"	94066643	17.5 - 25	TL	24	-	DB	52.8	17.7	23.6	159.8	33	281	14.00/1.5	-

STD: Standard - SPL: Special - DB: Dual Bead

Tolerances: O.D. ± 2% - O.W. ± 2% - RC ± 2.5% - LI/SS = Load Index / Speed Symbol; O.W. = Overall Width; O.D. = Overall Diameter; SLR = Static Loaded Radius; RC = Rolling Circumference