



AGRIMAX PROHARVEST

Description

AGRIMAX PROHARVEST is BKT's response to the current market needs in terms of combines and harvesting machines. The advanced VF (Very High Flexion) technology allows AGRIMAX PROHARVEST to carry 40% more load compared to standard tires with the same tire pressure minimizing soil compaction. Moreover, the three layers of steel belts combined with the cut and chip resistant compound ensure excellent puncture resistance, even on case of stubbles or crops leftovers on the field. The structure of the tire with a reinforced bead and a strong polyester carcass is synonym of durability and stability of the tire even during heavy duty operation.



UM

IS Standard

Construction

 Radial

Machinery

Agriculture ■ Harvester

Version	STEEL BELTED
Tire Type	TL
Tyre size	VF900/60R32
LI/SS	193;D

Dimensions IS Standard

SW (IS) (mm)	881
OD (IS) (mm)	1900
SLR (IS) (mm)	837
RC (IS) (mm)	5712
Rim Rec	DW 30 B
ECE	E11-106R-0010580

Load Capacity (IS)

km/h / bar	0.6	0.8	1.0	1.2	1.4	1.6	2.0	2.4	2.8	3.2
70	4085	4710	5340	6070	6700	7435	8270	8375	9735	10465
from 65 to 40	4485	5175	5865	6670	7360	8165	9085	9200	10695	11500
30	4575	5280	5985	6805	7510	8330	9270	9385	10910	11730
20	4665	5385	6100	6940	7655	8495	9450	9570	11125	11960
10	4935	5695	6455	7340	8100	8985	9995	10120	11765	12650
Upto 30 Cyc	5095	5875	6660	7575	8360	9270	10315	10445	12145	13055
Upto 15 Cyc	6080	7015	7950	9040	9975	11070	12315	12470	14495	15585
Upto 10 Cyc	6665	7690	8715	9910	10935	12130	13495	13665	15885	17080
10HT	4575	5280	5985	6805	7510	8330	9270	9385	10910	11730

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 28-02-2026

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..