



IS standard



GROWING TOGETHER

EARTHMAX

RADIAL OTR TIRES

SR 51



PRODUCT DATA SHEET



Radial

L-5

A2

229

Technologies



Extra Deep Tread

Performance



Traction



Cut Resistance



Stability



Durability



EARTHMAX SR 51

RADIAL OTR TIRES

EARTHMAX SR 51 (L-5) is an All Steel radial tire specially designed for loaders or dozers. EARTHMAX SR 51 is ideal for severe operations requiring added cut resistance, sidewall protection and exceptional traction.

Ø	Tire size	Type	TRA CODE	STAR RATING	LI/SS	Version	TKPH	O.W.	O.D.	SLR	RC	TREAD DEPTH (mm)	RIM	
								(mm)	(mm)	(mm)	(mm)		Rec.	Alt.
25"	17.5 R 25	TL	L-5	*	176 A2	CRC	-	437	1398	630	4110	61	14.00/1.5	-
	20.5 R 25	TL	L-5	*	186 A2	CRC	-	539	1545	703	4650	68	17.00/2.0	-
	23.5 R 25	TL	L-5	*	195 A2	CRC	-	612	1660	743	4882	77	19.50/2.5	-
	23.5 R 25	TL	L-5	**	201 A2	CRC	-	612	1660	743	4882	77	19.50/2.5	-
29"	29.5 R 29	TL	L-5	*	211 A2	CRC	-	777	1990	842	5872	94	25.00/3.5	24.00/3.5 ; 26.00/3.5
	875/65 R 29 (35/65 R 29)	TL	L-5	**	221 A2	CRC	-	878	1872	814	5616	92	27.00/3.5	27.00/3.0 ; 28.00/3.5
33"	35/65 R 33	TL	L-5	**	224 A2	CRC	-	905	2061	872	6082	95	28.00/3.5	-
	35/65 R 33	TL	L-5	***	229 A2	CRC	-	905	2061	872	6082	95	28.00/3.5	-

CRC: Cut Resistance Compound



Tolerances: O.D. ± 2% - O.W. ± 2% - RC ± 2.5% - LI/SS = Load Index / Speed Symbol; O.W. = Overall Width; O.D. = Overall Diameter; SLR = Static Loaded Radius; RC = Rolling Circumference