



IS standard



GROWING TOGETHER

EARTHMAX

RADIAL OTR TIRES

SR 22



PRODUCT DATA SHEET



Radial

G-2/L-2

B

201

Technologies



All Steel



Ice and Snow

Performance



Traction



Stability

EARTHMAX SR 22

RADIAL OTR TIRES



UK EARTHMAX SR 22 (G-2/L-2) is an *All Steel* radial tire specially designed for motor graders and loaders operating in extreme winter conditions on ice or snow. Operators will appreciate both excellent traction and stability provided by the large and non-directional tread design.

	Tire size	Type	TRA CODE	STAR RATING	LI/SS	Version	TKPH	O.W.	O.D.	SLR	RC	TREAD DEPTH (mm)	RIM	
								(mm)	(mm)	(mm)	(mm)		Rec.	Alt.
Ø 24"	14.00 R 24	TL	G-2/L-2	*	153 A8/ 175 A2	CRC	-	366	1370	625	4141	25	8.00 TG	9.00 GR; 10.00 VA
Ø 25"	15.5 R 25	TL	G-2/L-2	*	146 A8/ 169 A2	CRC	-	385	1275	557	3841	28	12.00/1.3	-
	17.5 R 25	TL	G-2/L-2	*	153 A8/ 176 A2	CRC	-	452	1350	590	3950	28	14.00/1.5	-
	17.5 R 25	TL	E-2/L-2	**	167 B/ 182 A2	CRC	-	452	1350	590	3950	28	14.00/1.5	-
	20.5 R 25	TL	G-2/L-2	*	161 A8/ 186 A2	CRC	-	525	1490	640	4315	32	17.00/2.0	17.00/1.7
	20.5 R 25	TL	E-2/L-2	**	177 B/ 193 A2	CRC	-	525	1490	640	4315	32	17.00/2.0	17.00/1.7
	23.5 R 25	TL	G-2/L-2	*	170 A8/ 195 A2	CRC	-	610	1614	709	4863	34	19.50/2.5	-
23.5 R 25	TL	E-2/L-2	**	185 B/ 201 A2	CRC	-	610	1614	709	4863	34	19.50/2.5	-	

CRC: Cut Resistant Compound



Tolerances: O.D. ± 2% - O.W. ± 2% - RC ± 2.5% - LI/SS = Load Index / Speed Symbol; O.W. = Overall Width; O.D. = Overall Diameter; SLR = Static Loaded Radius; RC = Rolling Circumference