



IS standard



GROWING TOGETHER

# AGRIMAX

RADIAL TRACTOR TIRES

## RT 657



PRODUCT DATA SHEET



Radial



# AGRIMAX RT 657

RADIAL TRACTOR TIRES



🇬🇧 AGRIMAX RT 657 is the ideal tire for on-the-road usage and soil tillage; some sizes are also suitable for vineyard harvesting. This tire guarantees excellent driving comfort as well as significant fuel savings. It has a high load capacity also at high speed levels. AGRIMAX RT 657 is the best choice for those who need a versatile and reliable tire, with no compromise on performance.

### Technologies



High Speed

### Performance



Reduced Soil Compaction



Handling and Comfort



Fuel Economy



Traction



High Load Capacity

	Tire size	LI/SS	RIM		S.W. (mm)	O.D. (mm)	SLR (mm)	RC (mm)	SRI (index)	Version
			Rec.	Alt.						
Ø 16"	320/65 R 16	117 D/120 A8	W 10	W 9 ; W 11	319	822	366	2466	390	STD
Ø 18"	320/65 R 18	109 A8/B	W 10	W 9 ; W 11	319	873	392	2587	425	STD
	320/65 R 18	125 A8/B	W 10	W 9 ; W 11	310	885	400	2667	425	STD
	340/65 R 18	113 A8/B	W 11	W 10 ; W 12	343	899	400	2667	425	STD
Ø 20"	340/65 R 20	124 D/127 A8	W 11	W 10 ; W 12	343	950	430	2892	450	STD
	420/65 R 20	135 D/138 A8	W 13	W 11 ; W 12	418	1054	468	3162	500	STD
	440/65 R 20	138 D/141 A8	W 14 L	W 13 ; W 15 L	441	1080	479	3240	525	STD
Ø 24"	420/65 R 24	138 D/141 A8	W 13	W 11 ; W 12	418	1156	519	3468	550	STD
	440/65 R 24	135 D/138 A8	W 14 L	W 13 ; W 15 L	441	1182	538	3546	575	STD
	440/65 R 24	135 D/138 A8	W 14 L	W 13 ; W 15 L	441	1182	538	3546	575	SPL
	480/65 R 24	140 D/143 A8	W 15 L	W 14 L	479	1234	562	3730	600	STD
	480/65 R 24	140 D/143 A8	W 15 L	W 14 L	479	1234	562	3730	600	SPL
	540/65 R 24	146 D/149 A8	W 16 L	W 18 L	530	1312	596	3942	625	STD
	540/65 R 24	146 D/149 A8	W 16 L	W 18 L	530	1312	590	3930	625	SPL

STD: Standard - SPL: Special

Tolerances: O.D. ± 2% - S.W. ± 2% - RC ± 2.5% - LI/SS = Load Index / Speed Symbol; S.W. = Section Width; O.D. = Overall Diameter; SLR = Static Loaded Radius; RC = Rolling Circumference; SRI = Speed Radius Index



Radial

R-1W

D

181

Technologies



High Speed

Performance



Reduced Soil Compaction



Handling and Comfort



Fuel Economy



Traction



High Load Capacity



	Tire size	LI/SS	RIM		S.W. (mm)	O.D. (mm)	SLR (mm)	RC (mm)	SRI (index)	Version
			Rec.	Alt.						
Ø 28"	420/65 R 28	135 D/138 A8	W 13	W 11 ; W 12	418	1257	584	3824	600	STD
	440/65 R 28	138 D/141 A8	W 14 L	W 13 ; W 15 L	441	1283	590	3927	625	STD
	480/65 R 28	142 D/145 A8	W 15 L	W 14 L	479	1335	610	4091	650	STD
	540/65 R 28	149 D/152 A8	W 16 L	W 18 L	530	1413	643	4253	675	STD
	540/65 R 28	149 D/152 A8	W 16 L	W 18 L	530	1413	643	4253	675	SPL
	600/65 R 28	154 D/157 A8	DW 20 B	W 18 L	611	1491	670	4470	700	STD
	600/65 R 28	154 D/157 A8	DW 20 B	W 18 L	611	1491	670	4470	700	SPL
Ø 30"	420/65 R 30	136 D/139 A8	W 13	W 11 ; W 12	418	1308	606	3952	625	STD
	540/65 R 30	150 D/153 A8	W 16 L	W 18 L	530	1464	670	4403	700	STD
	540/65 R 30	150 D/153 A8	W 16 L	W 18 L	530	1464	670	4403	700	SPL
	600/65 R 30	155 D/158 A8	DW 20 B	W 18 L	611	1542	697	4609	725	STD
Ø 34"	540/65 R 34	152 D/155 A8	W 16 L	W 18 L	530	1566	712	4742	750	STD
	540/65 R 34	152 D/155 A8	W 16 L	W 18 L	530	1566	712	4742	750	SPL
	600/65 R 34	157 D/160 A8	DW 20 B	W 18 L	611	1644	742	4960	775	STD

STD: Standard - SPL: Special

Tolerances: O.D. ± 2% - S.W. ± 2% - RC ± 2.5% - LI/SS = Load Index / Speed Symbol; S.W. = Section Width; O.D. = Overall Diameter; SLR = Static Loaded Radius; RC = Rolling Circumference; SRI = Speed Radius Index



Radial



Technologies



High Speed

Performance



Reduced Soil Compaction



Handling and Comfort



Fuel Economy



Traction



High Load Capacity



	Tire size	LI/SS	RIM		S.W. (mm)	O.D. (mm)	SLR (mm)	RC (mm)	SRI (index)	Version
			Rec.	Alt.						
Ø 34"	600/65 R 34	157 D/160 A8	DW 20 B	W 18 L	611	1644	742	4960	775	SPL
Ø 38"	540/65 R 38	153 D/156 A8	W 16 L	W 18 L	530	1667	760	5059	800	STD
	540/65 R 38	153 D/156 A8	W 16 L	W 18 L	530	1667	760	5059	800	SPL
	600/65 R 38	159 D/162 A8	DW 20 B	W 18 L	611	1745	790	5247	825	SPL
	600/65 R 38	159 D/162 A8	DW 20 B	W 18 L	611	1745	790	5247	825	STD
	650/65 R 38	163 D/166 A8	DW 20 B	DW 21 B ; DW 23 B	645	1811	830	5483	875	SPL
	650/65 R 38	163 D/166 A8	DW 20 B	DW 21 B ; DW 23 B	645	1811	830	5483	875	STD
	650/65 R 38	178 A8/175 B	DW 20 B	DW 21 B ; DW 23 B	645	1816	827	5488	875	SB
	900/55 R 38	179 D/181 A8	DW 27 B	DW 30 B	880	1950	880	5842	925	STD
Ø 42"	650/65 R 42	165 D/168 A8	DW 20 B	DW 21 B ; DW 23 B	645	1913	878	5810	925	STD

STD: Standard - SPL: Special - SB: Steel Belted



Tolerances: O.D. ± 2% - S.W. ± 2% - RC ± 2.5% - LI/SS = Load Index / Speed Symbol; S.W. = Section Width; O.D. = Overall Diameter; SLR = Static Loaded Radius; RC = Rolling Circumference; SRI = Speed Radius Index