



US standard



GROWING TOGETHER

# MULTIMAX

RADIAL MPT TIRES

## MP 522



PRODUCT DATA SHEET



Radial



A8/B



168

# MULTIMAX MP 522

RADIAL MPT TIRES



MULTIMAX MP 522 is the BKT multi-purpose tire developed for agro-industrial applications. It is suitable for all lifting and loading operations on vehicles such as telehandlers and compact loaders. Stability and traction are its strengths as well as outstanding puncture resistance. Thanks to its special compound, MULTIMAX MP 522 has an incredible cut and chip resistance.

### Technologies



Steel Belted



Special Compound

### Performance



Stability



Traction



High Puncture Resistance



Cut and Chip Resistance

	US CODE	Tire size	LI/SS	RIM		S.W. (In.)	O.D. (In.)	SLR (In.)	RC (In.)	TREAD DEPTH (32nds)	TIRE WEIGHT (lbs)	Version
				Rec.	Alt.							
Ø 18"	94045044	280/80 R 18 IND (10.5/80 R 18)	132 A8/B	W 9 ; 9 ; 9 SDC	W 8 ; W 10	11.1	35.7	16.6	108.2	42	94	STD
	94048793	340/80 R 18 IND (12.5/80 R 18)	143 A8/B	11 ; 11 SDC ; W 11	W 10 ; 12 ; 12 SDC	13.5	39.6	18.0	119.0	43	127	STD
Ø 20"	94052875	340/80 R 20 IND	144 A8/B	11	W 10 ; 11 SDC ; W 11 ; 12 ; 12 SDC	13.5	41.4	18.9	126.5	43	135	STD
	94045877	380/75 R 20 IND (14.5 R 20)	148 A8/B	W 12	W 11 ; 11 ; 12	15.1	42.3	19.0	128.0	47	162	STD
	94033829	400/70 R 20 IND (16.0/70 R 20)	149 A8/B	13	12 SDC ; 13 SDC ; 14	15.9	42.0	18.7	125.9	49	166	STD
Ø 24"	94051403	400/70 R 24 IND	152 A8/B	13	DW 12 ; 13 SDC ; DW 13 ; DW 13 L ; DW 14 L	15.9	46.1	21.0	138.9	49	183	STD
	94051397	400/80 R 24 IND (16.0/80 R 24)	162 A8/B	DW 13	DW 12 ; DW 13 L ; DW 14 L	15.9	49.2	22.2	149.1	47	195	STD
	94052257	440/80 R 24 IND	161 A8/B	DW 14 L	DW 13 ; DW 13 L ; DW 15 L	17.4	51.7	23.1	155.8	50	236	STD
	94031313	460/70 R 24 IND (17.5 L R 24)	159 A8/B	DW 15 L	DW 14 L ; DW 16 L	18.3	49.2	22.4	148.3	50	224	STD
	94032686	500/70 R 24 IND (19.5 L R 24)	164 A8/B	DW 16 L	DW 15 L ; DW 18 L	19.8	51.6	23.4	155.1	51	261	STD
	94052264	540/70 R 24 IND	168 A8/B	DW 16 L	DW 18 L	20.9	53.8	24.1	162.7	54	299	STD
Ø 26"	94052707	480/80 R 26 IND	160 A8/B	DW 15 L	DW 16 L	18.9	56.2	25.1	168.8	52	287	STD
	94073108	480/80 R 26 IND	167 A8/B	DW 15 L	DW 16 L	18.9	56.2	25.1	168.8	52	295	STD
Ø 28"	94052240	440/80 R 28 IND	156 A8/B	DW 14 L	DW 13 ; DW 13 L ; DW 15 L	17.4	55.7	25.3	168.4	50	263	STD

STD: Standard

Tolerances: O.D. ± 2% - S.W. ± 2% - RC ± 2.5% - LI/SS = Load Index / Speed Symbol; S.W. = Section Width; O.D. = Overall Diameter; SLR = Static Loaded Radius; RC = Rolling Circumference