



RIDEMAX IT 697 (M+S)



Description

RIDEMAX IT 697 M+S represents the best response to the needs of modern farming contractors during winter operations. It is perfect for haulage and municipality applications. This winter tire for tractors ensures extraordinary grip for all operations on icy and snowy roads without the need of snow chains being mounted. Thanks to the tread grooves and the strong casing, a tractor can be driven in full stability, also at high speed levels.

UM

US Standard

Construction

 Radial

Machinery

Agriculture ■ Tractor

Version	STANDARD
Tire Type	TL
Tyre size	540/70R24
LI/SS	170;D

Dimensions US Standard

USA Code	94072910
SW (US) (in)	21.1
OD (US) (in)	53.9
SLR (US) (in)	24.6
RC (US) (in)	164.6
Rim Rec	DW 16 L
Rim Alt	DW18 L
ECE	E11-106R-007933

Load Capacity (US)

mph / psi	17	23	29	35	41	46	52	58	65	73
40	4500	5560	6080	7140	8070	8990	9920	10850	12040	13230
30	4860	6010	6580	7720	8720	9720	10710	11720	13010	14290
25	5180	6390	7000	8220	9280	10350	11410	12480	13840	15210
20	5400	6670	7310	8580	9690	10800	11900	13020	14450	15870

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 28-02-2026

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..