



TR 882

Description

TR 882 is a very versatile tyre suitable for several applications and vehicles. It has been designed to fit implement machinery, hay harvesters/balers and sugar cane machinery. Engineered with a special compound to reduce damage, this tyre features also great durability and traction in every field condition. TR 882 is also available as "aramid-belted", "HD" and "special" versions to meet specific end user requirements.



UM

US Standard

Construction

◆ Bias

Machinery

Agriculture ■ ,Industrial & Construction ■ Trailer

Version	STANDARD
Tyre Type	TL
Tyre size	400/60-15.5
LI/SS	

Dimensions US Standard

USA Code	94019830
SW (in)	15.7
OD (in)	34.4
SLR (in)	14.9
RC (in)	102.6
Rim Rec	AG 13.00
ECE	E11-106R-004330

Load Capacity (US)

mph / psi	35
5 FR	6550
15 FR	5570
20 FR	5240
25 FR	4670
5 DW	4630
15 DW	3940
20 DW	3700
25 DW	3310

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 21-03-2026

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..