



## FL 630 SUPER

### Description

FL 630 SUPER is a flotation tire suitable for use with trailers, tankers and spreaders. Its radial construction provides excellent traction and perfect grip even in wet conditions, while maneuvering, while a reinforced bead and sidewall ensure durability.

### UM

IS Standard

### Construction

 Radial

### Machinery

Agriculture ■ Spreader



Version

STANDARD

Tire Type

TL

Tyre size

750/60R30.5

LI/SS

181;D

## Dimensions IS Standard

SW (IS) (mm)	754
OD (IS) (mm)	1675
SLR (IS) (mm)	746
RC (IS) (mm)	5115
Rim Rec	AG 24.00
ECE	E4-106R-001499

## Load Capacity (IS)

km/h / bar	0.8	1.0	1.2	1.6	2.0	2.4	2.8	3.2	3.6	4.0		
70	2405	2780	3155	3835	4435	5110	5785	6235	6910	7510		
65	2640	3055	3465	4210	4870	5610	6355	6850	7590	8250		
50	3200	3700	4195	5095	5895	6790	7690	8290	9190	9985		
40	3595	4155	4715	5725	6620	7630	8640	9315	10325	11220		
25	4175	4825	5475	6650	7695	8865	10040	10820	11995	13035		
10	4755	5500	6240	7575	8765	10100	11435	12330	13665	14850		

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different L

Printed on 24-02-2026

All product data contained in this publication are for information purposes only and may be modified at any time without notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for errors, omissions or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, distribute, sell, or otherwise use, in whole or in part, on paper format, electronic format or otherwise without prior written permission from Balkrishna Industries Ltd..