



## MP 585

### Description

MP 585 is an agro-industrial tire, which is suitable for multi-purpose vehicles in municipality/maintenance applications. This tire is specially engineered with a block pattern that offers maximum stability and durability in the most difficult working conditions, also at high speeds.

### UM

US Standard

### Construction

⊠ Bias

### Machinery

Agriculture ▪ Universal Vehicle, Industrial & Construction ▪ Universal Vehicle



Version	STANDARD
Tire Type	TL
Tyre size	10.5-20
LI/SS	

## Dimensions US Standard

USA Code	94038336
SW (US) (in)	10.7
OD (US) (in)	38.2
SLR (US) (in)	17.9
RC (US) (in)	113.8
Rim Rec	9
Rim Alt	9 SDC
ECE	E4-54R-0022631

## Load Capacity (US)

mph / psi	54
55	3970
30	4410

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 28-02-2026

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..